

 \blacktriangle This picture is for reference only, subject to the real thing !



Light weight, Small size



Cycle life up to 6000 times



Intelligent battery management system



 \bigcirc

Compatible with a variety of inverters

Support a variety of communication protocols, support RS485, RS232, CAN etc


In the extreme performance safety test, the battery will not catch fire, explode, leak, and be safer to use.



Basic Parameters
Nominal Voltage (V)
Nominal Capacity (Ah)
Energy (Wh)
Dimension (mm)
Weight (Kg)
Discharge Cut-off Voltage (V)
Charge Cut-off Voltage (V)
Communication Port
Cell serial number (pcs)
Working Temperature/°C
Design life
Cycle Life
Certification
Supports the max number of parallel connections
Maximum continuous charge current

Maximum continuous discharge current

HOME ENERGY STORAGE BATTERY **APPLICATION SYSTEM**



SUNBOOSTPOWER.COM ____

LFP-51.2V200AH
48/51.2
200
9800/10240
L690×W690×H186(226 Including hanger)
98/104
40.5(15S)/43.2(16S)
54.7(15S)/58.4(16S)
RS485,RS232 Can-bus-inverter
155/165
-10~60°C
>15 Years (25°C/77°F)
>6000, 25°C/77°F, 80%DOD
CE/UN38.3 UL9540,UL1973,CEC,IEC62619,
16
100A
100A

