




#### PRODUCT INTRODUCTION

Aluminium shutters are modern indoor and outdoor energy-saving sunshade product that perfectly comebine with practicality, protection and decoration function.

- Aluminium 6063, a green building material, which comply with policy of carbon peaking and neutrality, supporting the development of green buildings;
- ◆ Fixed and Operable Blade Options. Operable blade can provide variable control of light and ventilation. When the blades are openning to 90 degrees, the best ventilation is obtained.
- ◆ The airfoil double-layer blades improve bending strength, ensuring that the aluminium shutters have little deformation when impacted by external force, and achieve protection function.
- ◆ The ratio of visible & direct sunlight transmittance and UV transmittance all are 0.
  Blocks out UV and sunlight transmission.








Operable blade; Openning and closing 0°~180°; Dimming by refraction.

When blades openning to 90°;

Ventilation rate up to 80%; Create good ventilation condition. Airfoil double-layer blades; Made by aluminium 6063 Durable; Anti collision and theft,



**4 0** 


#### **APPLICATION**




#### Louvered Pergola
















#### Balcony

**• 04** 

#### **APPLICATION**

#### **Room Divider**

Sliding or bi-folding aluminium shutters can use as moveable room divider. Free conversiton between large and small space. Solve the problem of wall opacity and glass excessive light transmission. Can achieve divider, protection, shaiding, dimming, ventilation, privacy and beauty function at the same time.







High-end Private Club







#### Terrace Area Extending From The Building

As the medium of indoor and outdoor environment, it perfectly connects the building and outdoor space.



# High-class Office Building

The simple, high-end interior design and the comfort of light adjustment are not only a reflection of taste, but also conducive to the improvement of work concentration.







Vith Bi-tolding Shutters

### **APPLICATION**















# PRODUCT STYLE AND APPLICATION CASES











C Left &right U-channel



D H-channel




• 12——


### Sliding Shutters

Single panel dimension: 400mm-1350mm Numbe of tracks: Single, double, triple or others Standard configuration: Rolling sliding system Optional Accessory: Stainless steel flush bolt





### PRODUCT STYLE AND APPLICATION CASES



Stainless steel flush bolt



#### Bi-folding Shutters


Single panel dimension: 400mm-1350mm

Folding direction: All folded to one side / folded from the middle to both sides / special requirements.

Standard configuration: Aluminum hinge, pivot set, carrier system Optional Accessory: Stainless steel flush bolt, stainless steel hinge



### PRODUCT STYLE AND APPLICATION CASES



Stainless steel flush bolt


Stainless steel hinge




### Hinged shutters

Single panel dimension:400mm-800mm

Optional Accessory: Stainless steel handle lock, stainless steel hinge



# PRODUCT STYLE AND APPLICATION CASES



STANDARD COLOUR **MEASUREMENT** 

#### Surface treatment warranty of 10 years

#### Powder coating surface treatment











Gloss White YFS11002

Matte White YFS13001

Silver Gray YFS03001

Light Gray YFC32021

Dark Gray

YFC32020

Matte Black YFC80004

#### **Wood Grain Color**



OAK YFCM0068N

The color is for reference only, please prevail in kind.

\* Remarks: If used with our pergola, the color of the shutters can be consistent with the standard color of pergola.

Measuring method: top/middle/bottom, left/middle/right points (measuring H1, H2, H3, W1, W2, W3, total of 6 sizes)



\* Remarks: For installation in the opening, select the minimum value of width and height; For installation outside the opening, select the maximum value of width and height; If it is not square, it is best to contact our company to provide a solution.

REAL CASE























**-**∳ **21** 

REAL CASE




















PROJECT CASE

PROJECT CASE





25