


# GJYXCH FTTH Flame-retardant Self-Supporting Aerial Drop Cable

## Product Structure Diagram



## Product Description

Self-supporting drop optical cable includes central optical fiber(s) with 2 parallel steel wires as the strength members placed on both sides, and an additional strength member (steel wire). Finally a LSZH jacket is extruded outside.

## Product features

- Bending insensitivity fiber provides high bandwidth and excellent communication transmission property.
- Simple configuration, light weight and high tensile strength.
- Grooved design, easy to strip and splice, simplified installation and maintenance.
- Low smoke, zero halogen and flame retardant jacket, environment-Friendly.

## Application

FTTH Drop Cable.

## Technical Specifications

### Product Parameters

Project	Technical indicators			
Counts	1-4	6	8	12
Cable Diameter(mm)	2.0*5.0	2.0*5.2	2.8*6.2	2.8*6.2
Reference weight(Kg/km)	19.3	22.25	31.15	29.85
Fiber Type	G652D G657			
Tensile Strength(N)	Long/Short Term:300/600			
Crush Resistance(N/100mm)	Long/Short Term:1000/2200			
Bending Radius(mm)	Static/Dynamic:G652D:30D/60D:G657:20D/40D			
Temperature(°C)	Storage /Operation:-20°C~+70°C			