

# Fiber Protection Box 1 in 1 out

#### **Product Drawing**



#### **Product Description**

Mini Drop Cable Protect Box is used for drop cable connecting, splice and protection. It can hold 1pc SC simplex adapter, 2pcs SC fast connectors, suitable for FTTH. it is compact size, good appearance, provides extremely economical and optimal protection for exposed single fiber connectors.

Drop Cable Protect Box is used for drop cable connecting, splice and protection. The cable connection protection box for 1 in 1 out, for 2.0mm Fiber cable, 3.0mm Fiber cable Material: new ABS flame retardant, quality assurance, flame retardant performance in line with the communications industry standards, flame retardant grade UL94V-0.

Fiber cable Protection Box is used for drop cable connecting, splice and protection.Inside can install 1pc SC simplex adapter and 2pcs fast connector connection. The box is made of High quality ABS Material.Box cover and bottom utilize silicone rubber ring sealing. Both sides can lead in/out 2\*3mm FTTH drop cable or 3mm round cable.Wall-mount application,two installation hole distance is 150mm.

### **Product features**

- Made of high-quality PP plastic, silicone ring seal between the cover and the bottom.
- Both ends can go in and out of 2mm\*3mm FTTH cable or 3mm round cable.
- Protection class IP65.
- Light weight, compact size, can stick on wall anywhere with double faced adhesive tape or wall mounted.
- Small size, nice shape, convenient Installation.
- Splice contact protection is stable&reliable,Protect it from damage or broken by external force.

#### **Application**

Intermediate connection of optical cable lines.

Protection of fiber optic cable branch points.

Fiber optic cable protection in outdoor and harsh environments.

The application of FTTH system.

Fiber optic protection for data centers and communication rooms.



## **Product Parameters**

Project	Technical indicators
Product name	Fiber Protection Box 1 in 1 out
Lock type	Push lock or tubular lock
Material	ABS&PC alloy material
Dimensions(L*W*H )	160*46*17 mm
Capacity of Fiber	1 Fiber
Capacity of Splice	1 Core
Suitable Adapter	sc
Color	White or Black