

Fiber Protection Box 1 in 2 out

Product Drawing



Product Description

FTTH Inline Horizontal Optical Fiber Protection Box 2 In 2 Out Fiber Optic Splice Closure. It is widely used in the connection of optical fibers, and plays the role of sealing, protection, installation and storage of optical fiber connectors, etc. Advanced internal structure design, no fiber attenuation. The closure is spacious enough to wind and store fibers. Suitable for 2-core sheath wire or 3.0 diameter optical fiber Cable entry: 1 input port and 2 output ports.

Product features

- Advanced internal structure design, no fiber attenuation.
- The closure is spacious enough to wind and store fibers.
- Suitable for 2-core sheath wire or 3.0 diameter optical fiber.
- Cable entry: 1 input port and 2 output ports.

Application

Intermediate connection of optical cable lines.

Protection of fiber optic cable branch points.

Fiber optic cable protection in outdoor and harsh environments.

The application of FTTH system.

Fiber optic protection for data centers and communication rooms.

Technical Specifications

Product Parameters

Project	Technical indicators
Product name	Fiber Protection Box 1 in 2 out
Material	ABS
Waterproof grade	IP67
Dimensions(L*W*H)	180 x 70 x 20mm
Cable entry	1 input port and 2 output ports
Capacity of Splice	2 Core
Color	White or Black