



PM Plus

High-end Perimeter LED Screen Solution

PM Plus is upgraded new tech for perimeter LED screen, thin and light cabinets, 900mm height which is lower than standard perimeter LED screen, won't affect any sights of audiences. Meantime it has higher protection level IP67, wider and flatter, etc. New PM Plus product is usually used for football stadium, basketball stadium, baseball, hockey, ice-hockey, e-sport games and so on.

Brochure

Product Video

Installation Video

Contact

Aluminum Profile Cabinet

Thinner and lighter, 7.8cm thickness, 1600x900mm only 35kg/pcs.







High Quality Raw Material

LEDFUL uses Nationstar cooper wire LED lamps as standard, high brightness 6000~7000nits, stable performance, lower damage rate, longer lifetime.

4H Perfect Visual Effect

- High Brightness: ≥7000nits
- High Refresh Rates: ≥3840Hz
 High Grey Scale: 14~16 bits
- High Grey Scale: 14~16 bit
 High Contrast: ≥6000:1
- Tilgii Contrast. 20000. I






PM PLUS supports front maintenance and rear maintenance.


Special but simple maintenance tool makes quick addembly & disassembly and easy maintenance.

Dual Maintenance Ways



Upgraded Adjustable Bracket

Dest viewing angle for the addiences.






There are soft top cover on the top of each LED panel. And meantime the mask on the surface of LED display changed to soft rubber mask, these will protect the othletes from injury and also protect the screen

Great Protection Ability

those will protect the athletes from injury and also protect the screen well. It will be no problem if the screen are hit by the balls or other things by accidentally.



Safety Handle for Easy Moving





provide an escape exit.

Slide Rail for 90°Connection

LED cabinets can be easily connected by 90° via a slide rail. At the

same time, in the event of an emergency, it can be quickly opened to

be max 7,000nits~10,000nits which can let the LED screen still have a great performance under the strong sunshine.

Wider and Brighter


Screen

Real-time

Video converter

Maximum 160°C perfect viewing angle brings more audiences a

better viewing experience. Meantime the screen brightness can




Dual Signal & Power Backup PM PLUS series can do signal and power backup solution, if there is any damaged of power supply, receiver card or LAN cables, the

backup receiver card or power supply will connect and work normally,

problems, which is an important feature for some large sport events.

so the perimeter LED screen is still working normally without any

Nigeria National Stadium 260m Indoor Perimeter LED Screen for FIFA Game in Africa.



Model	PM8 PLUS		PM10 PLUS
Pixel Pitch(mm)	8.33		10
Pixel Matrix Per Sqm	144,115		10,000
Pixel Configuration	SMD3535		SMD3535
Brightness (nits)	6000		7000
Scan	1/3		1/2
IP Rate	IP65		IP65
Module Dimension		400×300mm / 1.31×0.98ft	
Cabinet Dimension		1600x900mm / 5.25x2.95ft	
Cabinet Material		Die Casting Aluminum	
Cabinet Weight		32KG	
Power Con. (W/sqm.)		Max. 650W / Avg.100~200W	
Service Access		Rear / Front	
Refresh Rate (HZ)		≥3840	
Grey Scale (bit)		16	
Contrast Ratio		5000:1	
Viewing Angle (H / V)		140° / 140°	
Operation Temperature		− 20 °C ~ +60 °C	
Input Voltage (AC)		AC110/240V, 50/60Hz	

* Specifications and photos are subject to change without prior notice.