RK400-14 Laser Snow Depth Sensor



RK400-14 has a large measuring range and high accuracy, with a maximum accuracy of 1mm. It also has super anti-interference ability and is widely used in various industrial control such as steel industry, metallurgical industry, automobile industry, printing industry, food industry, etc., and various field monitoring and inspection sites. The principle of the laser snow depth sensor is the optical triangulation method, and the semiconductor laser is focused on the measured object by the lens. The reflected light is collected by the lens and projected onto the CMOS array; the signal processor calculates the position of the light spot on the array through the trigonometric function to obtain the distance to the object.

FEATURES

- Easy installation
- High accuracy, good stability
- Maintenance-free
- Compact size for easy use
- Large range

APPLICATIONS

- Printing industry
- Metallurgical Industry
- Food industry
- Various industrial controls
- Various types of field monitoring and inspection sites.

SPECIFICATIONS

Item	Specification				
Range(1)	0-15m				
Laser characteristics	Red laser diode				
Wavelength	620nm~650nm				
Laser class	Level 2				
Spot type	Point				
Spot size	Spot light spot5mm@10m				
¢, or o⊫o	Line spot 3mm*150mm@10m				
Protection level	IP68				
Resolution	1mm				
Accuracy	±1cm				
Pow er consumption	<0.8W (without heating)				
Supply	12VDC				
Output	SDI-12				
Operating temperature	-40-+50°C				
Heating	Automatic, it can be turned on or off through commands				
Installation angle	Automatically calculate 0° and installation angle, <30° is allow ed				



RK400-14 Laser Snow Depth Sensor



www.rikasensor.com

Mounting	Include accessories of mounting to mast vertical of 4 inches of diameter				
Main material	White steel coated or sprayed				
Weight(unpacked)	2.5kg				

①The sensor has a 10cm measurement blind spot

PARAMETER SELECTION TABLE

Remark	Series	Туре	Output	Supply	Cable	
					Length	
RK						
	400					
		14				
			А			RS485
			В			RS232
			С			4-20mA
			D			0-5V
			E			Other
				А		9-18VDC
				Х		Other
					3000	Units:mm(typ.)
						Units:mm

Example: RK400-14AA4000 Output:RS485, Supply:9-18VDC, Cable Length:3m. Note: The cable conductors are identifiable by different colors.

> CE Complies with applicable CE directives. Specifications subject to change without notice. Version 1.3 Copyright © 2015 Hunan Rika Electronic Tech Co.,Ltd

Hunan Rika Electronic Tech Co., Ltd

Add: 10th Bd, International Enterprise Center, No.268 Xinxing Rd, Yuhua Dist, Changsha, 410116 Hunan, China.



info@rikasensor.com

www.rikasensor.com