

广州云利数码科技有限公司

Guangzhou Yunli Digital Technology Co., Ltd



网址: <https://yunli888.en.alibaba.com/>
 电话: +8615019806133
 地址: Room 1820, No. 518 Tianhe Road, Tianhe District,
 Guangzhou City

合作 · 共赢 · 创新 · 发展
 COOPERATION / WIN-WIN / INNOVATION / DEVELOPMENT

PORTABLE THERMAL PRINTER

MP-58MINI	01-02
MP-58M	03-04
MP-58C	05-06
MP-80M	07-08
MP-80L	09-10
MP-58H	11-12
MP-58H3	13-14
MP-58A	15-16
PT-260	17-18
15P1	19-20

T02	21-22
A6	23-24

DESKTOP THERMAL PRINTER

POS58D	27-28
POS58L	29-30
POS80L	31-32
POS80D	33-34
POS58B	35-36
POS58A	37-38
POS80L-1	39-40
POS8370	41-42
POS9200L	43-44
POS-8610	45-46

A42	47-48
A41L	49-50
TB41	51-52
M08F	53-54
VTR110	55-56
POS-9210	57-58
POS-9200	59-60
POS9200L	61-62
POS-9250	63-64
GD-88	65-66

PRODUCT CATALOG

COMPANY INTRODUCTION

With the independent R&D and manufacturing technology which combines with the international advanced technology in these years, our company has obtained more than 10 patents in the field of printers since its establishment. We are a domestic enterprise which has comprehensively mastered the core technology of printers and realized mass production

Guangzhou Yunli Digital Technology Co., Ltd. was established in April 2011 as an OEM factory specializing in the manufacturing and assembly of thermal printers. Due to the impact of the international environment, the company decided in November 2019 to transform and upgrade into a professional printer manufacturing enterprise that integrates research and development, production, sales, and service. We provide professional services to customers both domestically and internationally.



PORTABLE THERMAL PRINTER



Supermarket



Dining room



Pharmacy



Fruit store

Multi-industry application
Meet the needs of users from all walks of life

A6

79*79*42MM (W*D*H)



Phone direct, clear color

Compact body, Stylish appearance

Simple operation, Save technology

No ink required, Simple consumables

PRODUCT PARAMETER

Products Status	Stock
Interface Type	usb/bluethooth
Max Paper Size	58mm
Black Print Speed	50mm/s
Max. Resolution	203DPI
Brand Name	Eryin
Place of Origin	Fujian, China
Warranty(Year)	1-Year
Printing Method	Thermal Line Printing
Paper type	thermal paper, adhesive paper, label paper
Thermal Paper Roll Size	Max 58mm(W)*Max 30mm(D)
Command	compatible with POS/ESC command
Application scenarios	Offices, Classrooms,Hotels, gas stations, supermarkets...
Printing Content	English, Numbers, symbols, graphics, curves, ICONS...
Use	Photo Printer
Supply Ability	10000 Piece/Pieces per Month
Colour	Four options available
After-sales Service	Free spare parts

M110

114*87*63mm



Phone direct, clear color

Compact body, Stylish appearance

Simple operation, Save technology

No ink required, Simple consumables

PRODUCT PARAMETER

Product size	114*87*63mm
Power input	5V- 2A
Power supply mode	Micro USB, lithium battery
Name	Smart label printer
Printing technology	Thermal printing
Effective print width	48mm
Support consumables	"Three-proof synthetic thermosensitive label paper. Continuous paper
Consumables specification	20-50mm
Print speed	20-45-mm/s
Print density	1~15 gears can be adjusted
Print resolution	203dpi
Print head life	50km
Encounter interface	Bluetooth4.2, Micro USB
Battery capacity	1200mAh
Support operating system	Windows 7 / 8 / 10, Android, ISO
Instruction set	ESC/POS
Bar code	"Support one-dimensional bar code and two-dimensional code
Working environment	5C ~ 50°C

POS80L-1

160*128*120MM (W*D*H)



Long life



Simple operation



Large capacity
paper loading



Consumable
economy

PRODUCT PARAMETER

Print method	Line thermal printer
Paper width	80mm
Print width	74mm
Weight (g)	737g
Max diameter of paper roll	60mm thermal receipt
Dot per line	384 dots/line
Print speed	250mm/s
Life cycle time	100km(printing density under 12.5%)/ 100 million pulses
Text and graphic Support	English, figure, symbol, Chinese, graph, curve, icon pre-stored, barcode
Dot pitch (resolution)	203DPI/8 dots/mm
Interface	USB+serial/parallel/ethernet
Recharge adapter	DC24V/2.5A
Self-check	Without paper /low power/ cover open
Black mark test	Supported
Commands	ESC/POS compatible with order sets
Standard accessories	Long-term preservable paper, AC adapter
Operate setting	Temperature:-10~50; Humidity:20%~85%
Recharge Setting	Temperature:5~40; Humidity:20%~85%

POS8370

175*142*122 MM (W*D*H)



Long life



Simple operation



Large capacity
paper loading



Consumable
economy

PRODUCT PARAMETER

Print Method	Thermal printing
Interfaces	USB / USB+LAN / USB+ Bluetooth/ USB+LAN+ Bluetooth(optional)
Print Comand	ESC / POS command
Print Speed	220mm/s
Resolution	203DPI (8dot/mm)
TPH Reliability	100km
Auto Cutter	Partial
Cutter Life	1 million cuts
Logo	support downloading and printing logo
Line Spacing	3.75mm (Adjustable by commands)
Input Buffer	96K bytes
NV Flash	256K bytes
Driver	Win2003 / WinXP / Win7 / WIN8 / WIN10 / Linux ; Support IOS / Android
Power	Input: AC 110V/220V, 50~60Hz ; Output: DC 24V/2.5A
Paper Types	Thermal Roll Paper
Paper Width	79.5±0.5mm / φ 80 mm
Print Width	72mm
Paper Thickness	0.06-0.08 mm

POS9200L

225*162*106MM (W*D*H)



Long life



Simple operation



Large capacity
paper loading



Consumable
economy

PRODUCT PARAMETER

Application	Label print and other print
Interface Type	USB+Blue tooth
Max Paper Size	80mm
Black Print Speed	220mm/s
Color Print Speed	Non
Max. Resolution	203DPI,8 dots/mm
Brand Name	OEM
Life cycle time	50km(printing density under 12.5%)/100 million pulses
Warranty(Year)	1-Year
After-sales Service	Free spare parts
Software development kit	Yes
Accessory specification	Standard accessories
Printing method	Line Thermal printing
Interface	USB+Blue tooth
Power supply Input	24V/2.0A
Command set	ESC POS compatible commands
Weight	1.1 Kg
Supply Ability	10000 Set/Sets per Week

POS8610

186*145*136MM (W*D*H)



Long life



Simple operation



Large capacity
paper loading



Consumable
economy

PRODUCT PARAMETER

Interface Type	USB/Lan/Blue tooth/WIFI
Max Paper Size	80mm
Black Print Speed	220~300mm/sec
Color Print Speed	null
Max. Resolution	203dpi
Brand Name	Eryin
Place of Origin	Fujian, China
Warranty(Year)	1-Year
After-sales Service	Return and Replacement
Print Head Life	100km
Print Method	Direct Line Thermal
Print Speed	220~300mm/sec
Print Density	576 dots/ine
Effective Print Width	72mm
Line Spacing	3.75mm (Adjustable by commands)
Roll Diameter	83mm
Paper 1 Thickness	0.06-0.08mm
Cash Drawer Control	12V/1A

A42

262*80.7*46.8MM (W*D*H)



Long life



Simple operation



Large capacity
paper loading



Consumable
economy

PRODUCT PARAMETER

Weight	601g
Gross weight	About 0.87KG (excluding thermal paper)
Printing method	Thermal
Resolution	203DPI/300DPI
Interface	USB+ Bluetooth /USB+ Bluetooth +WIFI
Printing speed	10MM/S
Paper width	57mm-210mm
Print width	208MM
Media type (label)	Roll paper/folding paper
Dielectric thickness	0.05MM~0.15MM
Paper bin size	30MM
Outer box size	460*295*165mm
Sensor	Reflective
Bar codes	Support
2D Barcode	Support
Charging interface	Type C
Standby time	48 hours
Gross packing weight	About 7.50KG

M08F

310*68*41MM (W*D*H)



Long life



Simple operation



Large capacity
paper loading



Consumable
economy

PRODUCT PARAMETER

Printing technology	Thermal printing
Effective print width	216mm
Support consumables	Continuous thermal paper, self-adhesive, blue, eye protection, transparent, gold pink
Consumables specification	210mm
resolution ratio	203dpi
Print head life	50km
communication interface	Bluetooth 4.2/Type-C(蓝牙4.2/Type-C)
battery capacity	1200mAh
Support operating system	Phomemo: Android 5.0 / IOS 9.0
Power input	5V2A
power supply mode	Lithium battery
net weight	915g
Gross	964g
Package size	310x68x41mm
FCL size	370x300x235mm
FCL weight	11.568kg
Working environment	5°C ~ 45°C
Storage environment	-20°C ~ 60°C

POS-9210

180*226*147MM (W*D*H)



Long life



Simple operation



Large capacity
paper loading



Consumable
economy

PRODUCT PARAMETER

Interfaces	USB / LAN / Bluetooth (optional)
Print Comand	CPCLITSPLIESC
Print Method	Direct Line Thermal
Pirnt Speed	160mm/sec
Resolution	203DPI(8dot/mm)
Inner Code	Supported 11 types font size
Print parameters	Support to download the Logo trademark
Media Sensor	Dual-media sensors: transmissive and reflective
Operating Temperature	+0 C ~ 50 C (no condensation allowed)
Working Humidity	20% ~ 85% RH (no condensation allowed)
Two-dimensional code	QR Code.PDF417
Printer Driver	Win2003 / WinXP / Win7 / WIN8 / WIN10 / macOS Support IOS / Android
Thermal Paper Types	continuous paper, label paper, folded paper, tag paper
Effective Print Width	100mm (Max 800 points)
Available Max Paper Width	110±0.5mm
Paper Thickness	0.06-0.30 mm
Charging Method	external charger DC 24V/2.5A
Print Head	Reliability

POS-9200

180*115*107MM (W*D*H)



Long life



Simple operation



Large capacity
paper loading



Consumable
economy

PRODUCT PARAMETER

Interfaces	USB LAN Bluetooth (optional)
Print Method	Direct Line Thermal
Print Comand	CPCL1TSPLIESC
Print Speed	160mm/sec
Resolution	203DPI (8dot/mm)
Inner Code	Supported 11 types font size
Effective Print Width	100mm (Max 800 points)
Available Max Paper Width	110±0.5mm
Paper Thickness	0.06-0.30 mm
Charging Method	external charger DC 24V/2.5A
Print parameters	Support to download the Logo trademark
Media Sensor	Dual-media sensors: transmissive and reflective
One-dimensional code	UPC-A1 UPC-E JAN13 (EAN13)/ JAN8 (EAN8) CODE391 ITF ICODABAR / CODE93 / CODE128
Two-dimensional code	QR Code, PDF417
Printer Driver	Win2003 / WinXP 1 Win7 / WIN8 / WIN10 MACOS Support IOS Android
Thermal Paper Types	continuous paper, label paper, folded paper, tag paper
Print Head	Reliability
Print Reliability	100000000 pulse / dot or 50km

POS-9250

215*180*120MM (W*D*H)



Long life



Simple operation



Large capacity
paper loading



Consumable
economy

PRODUCT PARAMETER

Dimension	215*180*120mm
Black Print Speed	160mm/s
Style	Black and white
Use	Barcode Printer
After-sales Service	Return and Replacement, Call Center and on-line Technical Support
Paper type	thermal paper
Brand Name	OEM/ODM
Max. Resolution	203dpi
Unit Weight	1.55kgs (with accessories)
Max Paper Size	104MM
Private Mold	Yes
Printing Method	Thermal line printing
Interface	USB/LAN/BT/WIFI(Optional)
Print Speed	160mm/s(max)
Resolution	203DPI(8dot/mm)
Model	POS-9250
WARRANTY	1 year
Inner code	Supported 11 types font size

MP-58MINI

104*75*45MM (W*D*H)



Phone direct, clear color

Compact body, Stylish appearance

Simple operation, Save technology

No ink required, Simple consumables

PRODUCT PARAMETER

Print method	Line thermal printer
Paper width	58mm
Print width	48mm
Weight (g)	205g
Print speed	70mm/s
Life cycle time	30km(printing density under 12.5%)/100 million pulses
Text and graphic Support	English, figure, symbol, Chinese, graph, curve, icon pre-stored, barcode
Dot pitch (resolution)	203DPI/8 dots/mm
Interface	Type-C+ Bluetooth
Power	1500mAh 7.4V rechargeable Lithium battery
Recharge adapter	Stand by recharging / AC adapter 5V1A
Self-check	Without paper / low power/ cover open
Black mark test	Supported
Commands	ESC/POS compatible with order sets
Standard accessories	Long-term preservable paper, AC adapter, li-ion battery
Optional accessories	Leather coat
Weight/quantity of FCL	14.2kg/40 sets of products
Box gauge size	49.5*29.5*32.5CM



MP-58M

120*82*39MM (W*D*H)



Phone direct, clear color

Compact body, Stylish appearance

Simple operation, Save technology

No ink required, Simple consumables

PRODUCT PARAMETER

Weight	280g(without paper roll)
TPH	30km(not more than 12.5% printing desity)/100 million pulses
Emulation	ESC/POS compatible command set
Paper width	58mm
Paper thickness	60~80 m
Paper roller diameter	50mm
Driver	Windows XP/Win7/Win8/Win10
Printing Method	Thermal dot line printing
Resolution	203dpi,8dots/mm
Printing speed	70mm/s
Valid printing width	48mm
Interface	Type-C+ Bluetooth
Font	ASCII:9 17,12 24; Multiple code pages support
Battery	2000mAh/7.4V rechargeable lithium-ion battery
Charger	5V/1A in Adapter, 5v/500mA in computer USB connector
Recommeded paper	FD210.PD150R.PD160R
Weight/quantity of FCL	18kg/40 sets of products
Box gauge size	54.5*30*37 CM



MP-58C

103*75*45MM (W*D*H)



Phone direct, clear color

Compact body, Stylish appearance

Simple operation, Save technology

No ink required, Simple consumables

PRODUCT PARAMETER

Print method	Line thermal printer
Paper width	58mm
Print width	48mm
Weight (g)	200g
Max diameter of paper roll	40mm thermal receipt
Dot per lie	384 dots/line
Print speed	70mm/s
Life cycle time	30km(printing density under 12.5%)/100 million pulses
Text and graphic Support	English, figure, symbol, Chinese, graph, curve, icon pre-stored, barcode
Dot pitch (resolution)	203DPI/8 dots/mm
Interface	Type-C+ Bluetooth
Power	1500mAh 7.4V rechargeable Lithium battery
Recharge adapter	Stand by recharging / AC adapter 5V1A
Self-check	Without paper / low power/ cover open
Black mark test	Supported
Commands	ESC/POS compatible with order sets
Weight/quantity of FCL	13.5kg/40 sets of products
Box gauge size	49.5*27.5*32.5CM

MP-80L

109*125*63MM (W*D*H)



Phone direct, clear color

Compact body, Stylish appearance

Simple operation, Save technology

No ink required, Simple consumables

PRODUCT PARAMETER

Print method	Label printer (Receipt printer)
Paper width	80mm
Print width	30-72mm
Weight (g)	350g
Max diameter of paper roll	50mm thermal receipt
Print speed	70mm/s
Life cycle time	30km(printing density under 12.5%)/100 million pulses
Text and graphic support	English, figure, symbol, Chinese, graph, curve, icon pre-stored, barcode
Dot pitch (resolution)	203DPI/8 dots/mm
Interface	Type-C+ Bluetooth
Power	Direct supply power adapter 5V/1A
Recharge adapter	Stand by recharging / AC adapter
Self-check	Without paper / low power / cover open
Black mark test	ESC/POS compatible with order sets
Standard accessories	Long-term preservable paper, AC adapter
Optional accessories	Leather coat
Weight/quantity of FCL	24.1kg/40 sets of products
Box gauge size	55*38*35.5CM

MP-80M

109*125*63MM (W*D*H)



Phone direct, clear color

Compact body, Stylish appearance

Simple operation, Save technology

No ink required, Simple consumables

PRODUCT PARAMETER

Print method	Line thermal printer
Paper width	80mm
Print width	72mm
Weight (g)	350g
Max diameter of paper roll	50mm thermal receipt
Print speed	70mm/s
Life cycle time	30km(printing density under 12.5%)/100 million pulses
Text and graphic Support	English, figure, symbol, Chinese, graph, curve, icon pre-stored, barcode
Dot pitch (resolution)	203DPI/8 dots/mm
Interface	Type-C+ Bluetooth
Charging mode	5V/1A
Self-check	Without paper /low power/ cover open
Black mark test	Supported
Commands	ESC/POS compatible with order sets
Wireless Working Distance	Within 15m for Android device connection, within 30m for IOS Device connection
Weight/quantity of FCL	11kg/12 sets of products
Box gauge size	55*38*35.5CM

MP-58H3

108*80*37MM (W*D*H)



Phone direct, clear color

Compact body, Stylish appearance

Simple operation, Save technology

No ink required, Simple consumables

PRODUCT PARAMETER

Printing Method	Thermal dot line printing
Resolution	203dpi,8dots/mm
Printing speed	70mm/s
Valid printing width	48mm
Interface	Type-C+ Bluetooth
Font	ASCII:9 17,12 24; Multiple code pages support
Paper width	58mm
Paper thickness	60~80 m
Weight	252g
TPH	30km(not more than 12.5% printing desity)/100 million pulses
Emulation	ESC/POS compatible command set
Driver	Windows XP/Win7/Win8/Win10
Text and graphic Support	English, figure, symbol, Chinese, graph, curve, icon pre-stored, barcode
Battery	2000mAh/7.4V rechargeable lithium-ion battery
Charger	1)5V/1A in Adapter 2)5v/500mA in computer USB connector
Weight/quantity of FCL	15kg/40 sets of products
Box gauge size	49.5*29.5*32.5CM

MP-58H

108*80*37MM (W*D*H)



Fastener(Optional)



Phone direct, clear color

Compact body, Stylish appearance

Simple operation, Save technology

No ink required, Simple consumables

PRODUCT PARAMETER

Weight	252g
Resolution	203dpi,8dots/mm
Printing speed	70mm/s
Valid printing width	48mm
Interface	Type-C+ Bluetooth
Sleep mode	YES
Font	ASCII:9 17,12 24; Multiple code pages support
1D	UPC-A,UPC-E,EAN8,EAN13,CODE39,ITF,CODEBAR, CODE128,CODE93
2D	QR code
Sensors	Paper out detection
Charger	1)5V/1A in Adapter, 2)5v/500mA in computer USB connector
Battery	2000mAh/7.4V
Recommned paper	FD210.PD150R.PD160R
Paper width	58MM
Paper thickness	60~80M
Weight/quantity of FCL	16.6kg/40 sets of products
Box gauge size	49.5*29.5*32.5CM

MP-58A

83*83*35MM (W*D*H)



Phone direct, clear color

Compact body, Stylish appearance

Simple operation, Save technology

No ink required, Simple consumables

PRODUCT PARAMETER

Print method	Thermal, Inkless
Print Speed	50~60mm/sec in 203dpi
Paper width	58mm
Print width	48mm
Weight (g)	210g
Cutter	Integrated safety cutter
Input Charge	5V-1A
Power Supply	Built-in 2000mAh lithium battery
Thermal Paper Type	Notes thermal paper, Full sticker paper, Part sticker, Label paper
Black mark test	Supported
Mobile	Andriod 4.4 and newer, ios 8.0 and newer
System	Support Win 7, Win 8, Win 8.1, Win 10
Box size	90*44*112mm
Life cycle time	30km(printing density under 12.5%)/100 million pulses
Interface	Type-C + Bluetooth
Weight/quantity of FCL	17kg/80 sets of products
Box gauge size	50.5X38X38CM

MP-58N

108*80*30mm



Phone direct, clear color

Compact body, Stylish appearance

Simple operation, Save technology

No ink required, Simple consumables

PRODUCT PARAMETER

Dimension	108*80*30mm
Printing life	50km(not more than 12.5% printing density)/100 million pulses
Weight	174.5g (without paper roll)
Printing method	Thermal dot line printing
Resolution	203dpi,8dots/mm
Printing speed	50~80mm/s
Valid printing width	48mm
Interface	Bluetooth,Type-C
Charger	1) 5V/1A in Adapter, 2)5V/500mA in computer USB connector
Battery	2000mAh/3.7V Rechargeable lithium ion
Recommended paper	FD210,PD150R,PD160R
Paper width	58mm
Paper loading	Easy loading mechanism
Emulation	ESC/POS compatible command set
Driver	Windows XP/Win7/Win8/Win10
Weight/quantity of FCL	13.5kg/40 sets of products
Box gauge size	49.5X27.5X37.5CM

POS58D

178*127*105MM (W*D*H)



Long life



Simple operation



Large capacity
paper loading



Consumable
economy

PRODUCT PARAMETER

Print method	Line thermal printer
Paper width	58mm
Print width	48mm
Weight (g)	430g
Max diameter of paper roll	50mm thermal receipt
Print speed	70mm/s
Life cycle time	50km(printing density under 12.5%)/100 million pulses
Text and graphic Support	English, figure, symbol, Chinese, graph, curve, icon pre-stored, barcode
Dot pitch (resolution)	203DPI/8 dots/mm
Interface	Standard USB, Bluetooth
Power	Direct supply power adapter 9V/2A
Recharge adapter	Stand by recharging / AC adapter
Self-check	Without paper / low power / cover open
Black mark test	Supported
Commands	ESC/POS compatible with order sets
Standard accessories	Long-term preservable paper, AC adapter
Weight/quantity of FCL	9.3kg/12 sets of products
Box gauge size	42.5*38*27.5CM

POS58L

127*112*85MM (W*D*H)



Long life



Simple operation



Large capacity
paper loading



Consumable
economy

PRODUCT PARAMETER

Print method	Line thermal printer
Paper width	58mm
Print width	48mm
Weight (g)	330g
Max diameter of paper roll	50mm thermal receipt
Dot per line	384 dots/line
Print speed	70mm/s
Life cycle time	50km(printing density under 12.5%)/100 million pulses
Text and graphic Support	English, figure, symbol, Chinese, graph, curve, icon pre-stored, barcode
Dot pitch (resolution)	203DPI/8 dots/mm
Interface	Standard USB, Bluetooth
Charging mode	Direct supply power adapter 9V/2A
Self-check	Without paper /low power/ cover open
Black mark test	Supported
Commands	ESC/POS compatible with order sets
Wireless Working Distance	Within 15m for Android device connection, within 30m for IOS device connection
Weight/quantity of FCL	14.2kg/24 sets of products
Box gauge size	56*34*33cm

POS80L

195*145*144MM (W*D*H)



Long life



Simple operation



Large capacity
paper loading



Consumable
economy

PRODUCT PARAMETER

Print method	Line thermal printer
Paper width	80mm
Print width	72mm
Weight (g)	1.1KG
Max diameter of paper roll	60mm thermal receipt
Dot per line	384 dots/line
Print speed	250mm/s
Life cycle time	50km(printing density under 12.5%)/100 million pulses
Text and graphic Support	English, figure, symbol, Chinese, graph, curve, icon pre-stored, barcode
Dot pitch (resolution)	203DPI/8 dots/mm
Interface	USB+Serial/ Parallel/ Ethernet
Recharge adapter	DC24V/2.5A
Self-check	Without paper / low power/ cover open
Black mark test	Supported
Commands	ESC/POS compatible with order sets
Standard accessories	Long-term preservable paper, AC adapter
Weight/quantity of FCL	13.5kg/8 sets of products
Box gauge size	47.8*42.3*32.8 CM

POS80D

178*127*105MM (W*D*H)



Long life



Simple operation



Large capacity
paper loading



Consumable
economy

PRODUCT PARAMETER

Print method	Line thermal printer
Paper width	80mm
Print width	72mm
Weight (g)	460g
Max diameter of paper roll	50mm thermal receipt
Print speed	70mm/s
Life cycle time	50km(printing density under 12.5%)/100 million pulses
Text and graphic Support	English, figure, symbol, Chinese, graph, curve, icon pre-stored, barcode
Dot pitch (resolution)	203DPI/8 dots/mm
Interface	Standard USB, Bluetooth
Power	Direct supply power adapter 9V/3A
Recharge adapter	Stand by recharging / AC adapter
Self-check	Without paper / low power / cover open
Black mark test	Supported
Commands	ESC/POS compatible with order sets
Standard accessories	Long-term preservable paper, AC adapter
Weight/quantity of FCL	11kg/12 sets of products
Box gauge size	42.5*38*27.5CM

POS58A

157*125*108MM (W*D*H)



Long life



Simple operation



Large capacity
paper loading



Consumable
economy

PRODUCT PARAMETER

Print method	Line thermal printer
Paper width	58mm
Print width	48mm
Weight (g)	704g
Max diameter of paper roll	60mm thermal receipt
Dot per line	384 dots/line
Print speed	220mm/s
Life cycle time	50km(printing density under 12.5%)/100 million pulses
Text and graphic Support	English, figure, symbol, Chinese, graph, curve, icon pre-stored, barcode
Dot pitch (resolution)	203DPI/8 dots/mm
Interface	Standard USB / Bluetooth
Recharge adapter	9V3A
Self-check	Without paper / low power / cover open
Black mark test	Supported
Commands	ESC/POS compatible with order sets
Auto cutter	Yes
Weight/quantity of FCL	19km/ 18 sets of products
Box gauge size	57X51X24CM

MP-230

105*75*60mm



Phone direct, clear color

Compact body, Stylish appearance

Simple operation, Save technology

No ink required, Simple consumables

PRODUCT PARAMETER

Service life	50km(not more than 12.5% printing density)/100 million pulses
Weight	205.7g
Printing method	Thermal dot line printing
Resolution	203dpi,8dots/mm
Printing speed	30~50mm/s
Valid printing width	48mm
Interface	Bluetooth,Type-C
Font	ASCII:9 17,12 24;Multiple code pages support
1D	UPC-A,UPC-E,EAN8, EAN13, CODE39, ITF, CODEBAR, CODE128, CODE93
2D	QR code
Sensors	Paper out detection
Charger	1) 5V/1A in Adapter, 2)5V/500mA in computer USB connector
Battery	2000mAh/3.7V rechargeable lithium-ion battery
Recommended paper	FD210,PD150R,PD160R
Paper width	58mm
Weight/quantity of FCL	13.5kg/40 sets of products
Box gauge size	49.5*27.5*37.5CM

MP-58S

110*80*61mm



Phone direct, clear color

Compact body, Stylish appearance

Simple operation, Save technology

No ink required, Simple consumables

PRODUCT PARAMETER

Service life	50km(not more than 12.5% printing density)/100 million pulses
Weight	210.6g
Printing method	Thermal dot line printing
Resolution	203dpi,8dots/mm
Printing speed	30~50mm/s
Valid printing width	48mm
Interface	Bluetooth,Type-C
Font	ASCII:9 17,12 24;Multiple code pages support
1D	UPC-A,UPC-E,EAN8, EAN13, CODE39, ITF, CODEBAR, CODE128, CODE93
2D	QR code
Sensors	Paper out detection
Charger	1) 5V/1A in Adapter, 2)5V/500mA in computer USB connector
Battery	2000mAh/3.7V rechargeable lithium-ion battery
Recommended paper	FD210,PD150R,PD160R
Paper width	58mm
Weight/quantity of FCL	13.5kg/40 sets of products
Box gauge size	49.5*27.5*37.5CM

POS58B

156*115*90MM (W*D*H)



Long life



Simple operation



Large capacity
paper loading



Consumable
economy

PRODUCT PARAMETER

Print method	Line thermal printer
Paper width	58mm
Print width	48mm
Weight (g)	310g
Max diameter of paper roll	50mm thermal receipt
Print speed	70mm/s
Life cycle time	50km(printing density under 12.5%)/100 million pulses
Text and graphic support	English, figure, symbol, Chinese, graph, curve, icon pre-stored, barcode
Dot pitch (resolution)	203DPI/8 dots/mm
Interface	Standard USB, Bluetooth
Power	Direct supply power adapter 9V/2A
Recharge adapter	Convenient charging / AC adapter
Self-check	Without paper / low power / cover open
Black mark test	Supported
Commands	ESC/POS compatible with order sets
Standard accessories	Adapter, thermal paper, USB, instruction manual
Weight/quantity of FCL	12.7kg/20 sets of products
Box gauge size	55*35*34CM

MP-58C1

109*80*48MM



Phone direct, clear color

Compact body, Stylish appearance

Simple operation, Save technology

No ink required, Simple consumables

PRODUCT PARAMETER

Dimensions	109*80*48mm
Weight	172.3g(without paper roll)
Printing method	Thermal dot line printing
Resolution	203dpi,8dots/mm
Printing speed	50~80mm/s
Valid printing width	48mm
Interface	Bluetooth, USB(optional)
Recommended paper	FD210,PD150R,PD160R
Width of paper	58mm
Thickness of paper	60-75μm
Diameter of paper roll	≤40mm
Paper installation	Easy loading mechanism
1D	"UPC-A,UPC-E,EAN8, EAN13, CODE39, ITF,
2D	CODEBAR,CODE128,CODE93"
Current of charge	QR code
Battery	Adapter: Max. 5V 1A
Print life	Computer USB: 5V 500MA Max
	2000mAh/ 3.7v rechargeable lithium-ion battery

MP-58C2

109*80*48MM



Phone direct, clear color

Compact body, Stylish appearance

Simple operation, Save technology

No ink required, Simple consumables

PRODUCT PARAMETER

Dimensions	109*80*48mm
Weight	172.3g(without paper roll)
Printing method	Thermal dot line printing
Resolution	203dpi,8dots/mm
Printing speed	50~80mm/s
Valid printing width	48mm
Interface	Bluetooth, USB(optional)
Recommended paper	FD210,PD150R,PD160R
Width of paper	58mm
Thickness of paper	60-75μm
Diameter of paper roll	≤40mm
Paper installation	Easy loading mechanism
1D	"UPC-A,UPC-E,EAN8, EAN13, CODE39, ITF,
2D	CODEBAR,CODE128,CODE93"
Current of charge	QR code
Battery	Adapter: Max. 5V 1A
Print life	Computer USB: 5V 500MA Max
	2000mAh/ 3.7v rechargeable lithium-ion battery

MP-58T

127.5*88*64.7MM



Phone direct, clear color

Compact body, Stylish appearance

Simple operation, Save technology

No ink required, Simple consumables

PRODUCT PARAMETER

Weight	280.4g(Does not contain thermal paper)
Printing method	Thermal dot line printing (Label printer)
Resolution	203dpi,8dots/mm
Printing speed	50~80mm/s
Valid printing width	48mm
Interface	Bluetooth, USB(optional)
Recommended paper	FD210,PD150R,PD160R
Width of paper	58mm
Thickness of paper	60-75μm
Diameter of paper roll	≤50mm
Current of charge	Adapter: Max. 5V 1A Computer USB: 5V 500MA Max
Battery	2000mAh/ 7.4v rechargeable lithium-ion battery
Print life	50 km (print density not exceeding 12.5%)/ 100 million pulses"
Print command	Compatible with ESC/POS commands
Working conditions	Working temperature: 0~50° C, working humidity: 20~85%
Storage conditions	Storage temperature: -10~70° C, storage humidity: 10~90%
Print command	Compatible with ESC/POS commands

GD-88

290*130*80MM



Long life



Simple operation



Large capacity
paper loading



Consumable
economy

PRODUCT PARAMETER

Dimension	290*130*80mm
Printing Method	Thermal Direct
Printing Resolution	203dpi, 8dots/mm
Printing Speed	25mm/s Max
Printing Width	216mm
Printing Life	30KM
Paper media	A4 Stack Type Thermal Paper, Roll Type Thermal Paper
Paper Width	≤216mm
Paper Thickness	0.08-0.2mm
Lithium Battery	2600mAh Li-On rechargeable
Power Adaptor	DC 5V/2A
Interface	USB+BT
Working Temperature/Humidity	-10~50/ 10~90% (Non-condensing)
Storage Temperature/Humidity	-40~80/ 5~95% (Non-condensing)
Brand Name	Eryin

POS80AL

168X133X124mm(LxWxH)



Long life



Simple operation



Large capacity
paper loading



Consumable
economy

PRODUCT PARAMETER

Printing Method	Thermal Printing
Dot Density	8dots/mm,576dots/line
Print Speed	160mm/s(25% print density)
Paper Width	79.5mm±0.5mm
Western/Chinese	12x24dots
Interface	USB,U+BT,U+WiFi,U+Network
Supported Functions	Out-of-paper alarm, overheat protection, (Option: real voice, sound and light alarm)
Money Box Control	DC24V,1A,6-wire RJ-11 socket
Power Requirements	DC24V,1.25A
Paper Type	Ordinary thermal paper 79.5x80mm(MAX)
Paper Thickness	0.06~0.08mm
Maximum Outside Diameter	φ80mm
Minimum Inner Diameter	φ13mm
Paper loading method	Simple paper loading
Cutting Method	Half-cut
Printhead Life	100km
Cutter life	1,000,000 times
Product Net Weight (Single)	0.83KG

POS830B

136X174X128mm(LxWxH)



Long life



Simple operation



Large capacity
paper loading



Consumable
economy

PRODUCT PARAMETER

Dot Density	8 dots/mm,576 dots/line
Print Speed	160mm/s(25% print density)
Paper Width	79.5 mm ± 0.5 mm
Western/Chinese	12x24 dots
Interface	USB,U+BT,U+WiFi,U+Net,U+Net+Serial
Supported Functions	Out of paper alarm, overheating protection, (Option: real voice)
Money Box Control	DC 24V,1A, 6-wire RJ-11 socket
Power Requirements	DC 24V,1.25A
Paper Type	Ordinary thermal paper 79.5x80mm(MAX)
Paper Thickness	0.06-0.08mm
Maximum Outer Diameter.	Medium 80mm
Minimum Inner Diameter	Medium 13mm
Paper loading method	Simple paper loading
Cutting Method	Half-cut
Printhead Life	100km
Cutter life	1,000,000 times
Operating Temperature/Humidity	Operating temperature:0~50°C, operating relative humidity:10~80%
Storage Temperature/Humidity	Storage temperature:-20~60°C, storage relative humidity:10~90%

POS-A401

276.6*104.6*74MM



Long life



Simple operation



Large capacity
paper loading



Consumable
economy

PRODUCT PARAMETER

Printer Dimension	276.6*104.6*74mm
Unit Weight	1.06kgs(with accessories)
Interfaces	Bluetooth, USB Type-C (charging function, printing function)
Print Method	Direct Line Thermal
Rechargeable Li-battery	2600 mAh
Print Speed	50mm/sec
Print Resolution	203DPI(300DPI max)
Print Life	50KM
Document	Support word, excel, pdf, txt, ppt and other format files printing
Print Width	216mm (max)
Black mark detection	YES
Paper detection	YES
Alarm function	Paper out detection ,Low battery detection
Printer Driver	Windows OS; Support IOS/Android
Thermal Paper(Roll paper)	Continuous paper, Black label paper, Tattoo paper

MP-805

130.7*119.3*60mm



Phone direct, clear color

Compact body, Stylish appearance

Simple operation, Save technology

No ink required, Simple consumables

PRODUCT PARAMETER

Dimension	130.7*119.3*60mm
Weight (g)	409g
Printing method	Thermal Printing
Interfaces	USB-Type-C Bluetooth2.0/4.0
max paper size	80mm
Adapter	Input:220V.50HZ Output:5V.1A
Power supply	2600MAH rechargeable lithium polymer battery
Resolution	8dots/mm(203DPI).576dots/Line
black print speed	50-80mm/s
Print Reliability	10000000 pulse / dot or 50 km
Paper Out Detection	When the paper runs out the printer function indicator (red light) will blink and the buzzer will indicate
Printable content	Chinese characters (GBK supported). International character sets, ascii characters, a number of half-width customized characters, barcodes CODE39, EAN13, CODABAR, CODE93, ITF, CODE128, 1D codes, 2D codes, graphics.
Print width	72mm (adjustable from 25 to 72mm)

S1

88*88*43MM



Phone direct, clear color

Compact body, Stylish appearance

Simple operation, Save technology

No ink required, Simple consumables

PRODUCT PARAMETER

Dimension	88*88*43mm
Weight (g)	172g (excluding thermal paper)
Printing method	Thermal Printing
Interfaces	USB-Type-C Bluetooth
Size of the liquid crystal screen	2.0-inch high-definition screen
Storage medium	TF memory card
Lithium battery	1300mAh
Video resolution	1080P/30FPS
Battery life	Take photos for 4 hours; Video recording for 2 hours Standby for 6 months
Memory card	32gb
Function	Games, timing, profile pictures, video recording, filters, taking photos, continuous shooting, printing photos

MP-L 1

82*82*40mm



Phone direct, clear color

Compact body, Stylish appearance

Simple operation, Save technology

No ink required, Simple consumables



PRODUCT PARAMETER

Size	80*80*40mm
Weight	109.7g
Printing method	Thermal dot line printing
Resolution	96dpi,8dots/cm
Printing speed	30-50mm's
Valid printing width	12mm
Interface	Bluetooth
Battery	1100mAh/3.7v
Current of charge	Adapter:Max5V1A Computer USB: 5V 500MA Max
Recommended paper	FD210,PD150R,PD160R
Width of paper	15mm
Thickness of paper	60-75μm
Diameter of paper roll	≤30mm
Paper installation	Easy loading mechanism
Lack of paper detection	Paper run out detection

T1

90*75*38mm



Phone direct, clear color

Compact body, Stylish appearance

Simple operation, Save technology

No ink required, Simple consumables

PRODUCT PARAMETER

Weight	142.1g
Printing method	Thermal dot line printing
Resolution	203dpi,8dots/mm
Printing speed	30-50mm's
Valid printing width	48mm
Interface	Bluetooth, USB
Recommended paper	FD210,PD150R,PD160R
Width of paper	57mm
Thickness of paper	60-75μm
Diameter of paper roll	≤30mm
Paper installation	Easy loading mechanism
Lack of paper detection	Paper run out detection
Battery	1200mAh/3.7v
Power supply	Blue indicator light
Bluetooth	Blue indicator light
Charging	Yellow indicator light
Current of charge	Adapter: Max 5V1A Computer USB:5V 500MA Max

T2

82*82*40mm



Phone direct, clear color

Compact body, Stylish appearance

Simple operation, Save technology

No ink required, Simple consumables

PRODUCT PARAMETER

Weight	133.1g
Printing method	Thermal dot line printing
Resolution	203dpi,8dots/mm
Printing speed	30-50mm's
Valid printing width	48mm
Interface	Bluetooth, USB
Recommended paper	FD210,PD150R,PD160R
Width of paper	57mm
Thickness of paper	60-75μm
Diameter of paper roll	≤30mm
Paper installation	Easy loading mechanism
Lack of paper detection	Paper run out detection
Battery	1200mAh/3.7v
Power supply	Blue indicator light
Bluetooth	Blue indicator light
Charging	Yellow indicator light
Current of charge	Adapter: Max 5V1A Computer USB:5V 500MA Max

T3

78*78*40mm



Phone direct, clear color

Compact body, Stylish appearance

Simple operation, Save technology

No ink required, Simple consumables

PRODUCT PARAMETER

Weight	139.5g
Printing method	Thermal dot line printing
Resolution	203dpi,8dots/mm
Printing speed	30-50mm's
Valid printing width	48mm
Interface	Bluetooth, USB
Recommended paper	FD210,PD150R,PD160R
Width of paper	57mm
Thickness of paper	60-75 μ m
Diameter of paper roll	\leq 30mm
Paper installation	Easy loading mechanism
Lack of paper detection	Paper run out detection
Battery	1200mAh/3.7v
Power supply	Blue indicator light
Bluetooth	Blue indicator light
Charging	Yellow indicator light
Current of charge	Adapter: Max 5V1A Computer USB:5V 500MA Max

POS-9220

180*115*107MM (W*D*H)



Long life



Simple operation



Large capacity
paper loading



Consumable
economy

PRODUCT PARAMETER

interface type	USB / LAN / BT /WIFI
max paper size	110mm
black print speed	160mm/s
software development kit (sdk)	Yes
Printer Dimension	180*115*107mm
Unit Weight	1.9 kgs (with accessories)
Pieces Per CTN	8 Pieces (with paper stand)
Interfaces	USB / LAN / Bluetooth(optional)
Resolution	203DPI(8dot/mm)
Inner Code	Supported 11 types font size
Print parameters	Support to download the Logo trademark
Thermal Paper Types	continuous paper, label paper, folded paper, tag paper
Charging Method	external charger DC 24V/2.5A
Print Reliability	100000000 pulse / dot or 50km

MP-5810

107*75*52MM



Phone direct, clear color

Compact body, Stylish appearance

Simple operation, Save technology

No ink required, Simple consumables

PRODUCT PARAMETER

Printing Method	Thermal Line Printing
Printing Speed	90mm/sec (Max)
Reliability	50km
Unit Weight	400g(including standard accessories)
Resolution	203dpi(8dots/mm)
Paper Type	Thermal Roll Paper
Paper Width	58mm
Effective Printing Width	48mm (384 dots/line)
Line Spacing	3.75mm (Adjustable by commands)
Li-Battery	7.4V/1500mAh
Roll Diameter	φ≤45mm
Paper Thickness	0.06-0.08mm
Communicacions	USB (Type C)+Bluetooth 4.0
Printing Command	ESC/POS
Character Size	ANK,FontA:1.5x3.0mm(12x24 dots) Font B: 1.1x2.1mm (9x17 dots)...
One-dimensional code	UPC-A/UPC-E/ JAN13(EAN13)/ JAN8 (EAN8) / CODE39/ITF/CODABAR...
Two-dimensional code	QR Code,PDF417
Input Buffer	32K bytes

POS-9260

180*78*75MM



Long life



Simple operation



Large capacity
paper loading



Consumable
economy

PRODUCT PARAMETER

Print Method	Direct Line Thermal
Unit Weight	800g (with accessories)
Charging Method	external charger DC 24V/2.5A
Print Reliability	10000000 pulse / dot or 50km
Available paper width	30-110mm (Max 832 points)
Maximum effective width	104mm
Interfaces	USB / Bluetooth / WIFI(optional)
Print Comand	TSPL/CPCL command (ESC/POS command)
Pirnt Speed	160mm/sec (MAX)
Resolution	203DPI (8dot/mm)
Inner Code	Supported 11 types font size
Print parameters	Support to download the Logo trademark
Media Sensor	Dual-media sensors: transmissive and reflective
One-dimensional code	UPC-A / UPC-E / JAN13 (EAN13) / JAN8 (EAN8) / CODE39 / ITF / CODABAR...
Two-dimensional code	QR Code, PDF417
Printer Driver	Win2003 / WinXP / Win7 / WIN8 / WIN10 / WIN11/MACOS ; Support IOS / Android
Thermal Paper Types	continuous paper, label paper, folded paper, tag paper
Paper Thickness	0.06-0.30 mm

MP-58X1

108*80*30mm



Phone direct, clear color

Compact body, Stylish appearance

Simple operation, Save technology

No ink required, Simple consumables

PRODUCT PARAMETER

Dimension	108*80*30mm
Printing life	50km(not more than 12.5% printing density)/100 million pulses
Weight	174.5g (without paper roll)
Printing method	Thermal dot line printing
Resolution	203dpi,8dots/mm
Printing speed	50~80mm/s
Valid printing width	48mm
Interface	Bluetooth,Type-C
Charger	1) 5V/1A in Adapter, 2)5V/500mA in computer USB connector
Battery	2000mAh/3.7V Rechargeable lithium ion
Recommended paper	FD210,PD150R,PD160R
Paper width	58mm
Paper loading	Easy loading mechanism
Emulation	ESC/POS compatible command set
Driver	Windows XP/Win7/Win8/Win10
Weight/quantity of FCL	13.5kg/40 sets of products
Box gauge size	49.5X27.5X37.5CM

MP-260

120*85*40mm



Phone direct, clear color

Compact body, Stylish appearance

Simple operation, Save technology

No ink required, Simple consumables

PRODUCT PARAMETER

Weight	235.9 (Net weight)
Printing method	Thermal dot line printing
Resolution	203dpi,8dots/mm
Printing speed	50~80mm/s
Valid printing width	25mm-50mm
Interface	Bluetooth, USB(optional)
Recommended paper	FD210,PD150R,PD160R
Width of paper	58mm
TPH	50 km (print density not exceeding 12.5%)/ 100 million pulses
Diameter of paper roll	≤50mm
Battery	2000mAh/ 7.4v rechargeable lithium-ion battery
Current of charge	Adapter: Max. 5V 1A
	Computer USB: 5V 500MA Max
Thickness of paper	60-75μm
Working conditions	Working temperature: 0~50° C, working humidity: 20~85%
Storage conditions	Storage temperature: -10~70° C, storage humidity: 10~90%
Actuation	Windows XP/Win7/Win8/Win10/Win11
Print command	Compatible with ESC/POS commands

L12

108*100*56mm



Phone direct, clear color

Compact body, Stylish appearance

Simple operation, Save technology

No ink required, Simple consumables

PRODUCT PARAMETER

Printing method	Thermal printing 15mm/s
Printing speed	203dpi
Resolution	50km
TPH mileage	Label paper
Thermal paper type	15mm (MAX) 1200mAh
Printing width	Mobile phone Bluetooth, USB (Type-C) 220g
Rechargeable lithium battery Interface	CE,FCC,ROHS
Weight of a single unit	Stickers (5-meter installation paper)
Certification Certificate Consumables	1 sticker, 1 instruction manual, 1 data cable, 1 color box
Assembly List Packaging	60 units per box
Box Specifications	41.5*33.2*29 cm
Box weight	13.2 kg
Paper thickness	60 - 150 μ m Paper-cutting
method	Hand tearing
Alarm function	Paper shortage detection, battery low charge detection

A41

265*58*30MM (W*D*H)



Long life



Simple operation



Large capacity
paper loading



Consumable
economy

PRODUCT PARAMETER

Product name	Portable Bluetooth Tattoo Printer
Product weight	475g
Print speed	150mm/s
Print type	Thermal printing
Print head life	50km
Input voltage	DC 5V/2A
Interface Type	Bluetooth
Battery capacity	2000mah(7.4V)
Automatic shut-down	30min
Standby time	About 30 days
Charging time	About 1.30H
Continuous printing	90 sheets of tattoo printing paper
Paper width specifications	210mm or 218mm
Charging port	Type-C
Carton size	430*305*233 MM

POS-A4MINI

174.7*141.7*122.3MM



Long life



Simple operation



Large capacity
paper loading



Consumable
economy

PRODUCT PARAMETER

Printer Dimension	174.7*141.7*122.3(mm)	
Unit Weight	1.48 kg (With Accessories)	
Power Supply	DC 24V/1.5A	
Rechargeable Li-battery	2600 mAh	
Interfaces	USB+Bluetooth+WIFI+Cloud (optional)	
Print Method	Thermal printing	
Print Speed	Charging: 70mm/s	Battery: 50mm/s
Print Resolution	300 DPI	
TPH Life	100km	
Black mark detection	Yes	
Paper detection	Yes	
Paper Width	210mm(roll paper)	
CTN Weight	12.6 kg	
Pieces Per CTN	8 Pieces	
Status indication	Communication mode, Printing, Out of paper,Printer Setting	
TFT display	Net Status,Select Paper type	

D82

266x82x50mm



Phone direct, clear color

Compact body, Stylish appearance

Simple operation, Save technology

No ink required, Simple consumables

PRODUCT PARAMETERS

Print Type	Thermal Printing
Power Supply	1800mAh/7.4V
Supported Systems	Android/iOS/Windows
Print Area	A4/57mm/77mm/107mm
Interface	Bluetooth
Input	5V 2A
Connector	USB (Type-C)
Resolution	203dpi
Print Media	Labels
Paper Capacity	Roll Paper, Folded Paper
Net Weight	680g
Application	Text Printing

P11

75*70*30mm



Phone direct, clear color

Compact body, Stylish appearance

Simple operation, Save technology

No ink required, Simple consumables

PRODUCT PARAMETER

Size	75*70*30mm
Weight	111.8g (No paper)
Printing method	Thermal dot line printing
Resolution	96dpi,8dots/rm
Printing speed	10mm's
Valid printing width	15mm*30
Interface	Bluetooth
Battery	1200mAh/3.7v
Current of charge	Adapter: Max5V1A Computer USB: 5V 500MA Max
Recommended paper	FD210,PD150R,PD160R
Width of paper	15mm

GD-80

265*80*48mm



Phone direct, clear color

Compact body, Stylish appearance

Simple operation, Save technology

No ink required, Simple consumables

PRODUCT PARAMETERS

Printing Method	Thermal printing
Net Weight	655g
Interfaces	Bluetooth, USB (Type-C)
Effective Print Width	216mm (Max)
Print Density	203DPI
Print Speed	16mm/s (12.5% coverage, medium density)
Paper Width	57-210mm (GB standard), 57-216mm (US Standard)
Printhead Life	30KM
Supported Paper Types	Thermal roll paper/Thermal fanfold paper
Battery Type	Lithium battery 7.4V
Battery Capacity	1500mAh
Input Voltage	DC 5V/2A
Accessories	Manual, Type-C data cable, Certificate of Conformity, Thermal paper