



It's More Than A Printer





ZY-608

Thermal Receipt Printer



300mm/s high-speed printing.
Paper loading and dispensing front type.
82mm ultra-large capacity paper bin, supporting 58, 80 width printing paper.
Visual LED display light, real-time prompt of power supply, error report and paper shortage.
Support IAP online upgrade, support a variety of one-dimensional and two-dimensional bar code printing.
100M network port, supporting network printing status monitoring.

ZY-608

Thermal Receipt Printer



Model	ZY608
Printing	
Print Method	Direct Thermal
Print Speed	300mm/s
Resolution	203dpi
Printing Width	72mm(default)80mm(Max)
Discharge direction	"Top paper" and "front paper" can be adjusted in both directions"
Paper separator (option)	58mm (57.5 ± 0.5mm)80mm (79.5 ±0.5mm)
Interface	USB+Rs232+LAN/USB+Rs232+LAN+WIFI/BT (optional)
Page Mode	Support
Memory	
Input buffer	4M
NV Flash	256kbytes
Fonts	Font A12x24 Font B 9x17
Chinese	GB18030,BIG5 24x24dots
Character Size (mm)	Font A: 1.5×3.0mm; Font B: 1.1×2.1mm; Simple/Traditional: 3.0×3.0mm Japanese/KoreaJapanese JIS、 Korean KSC5601 (optional)
User-defined	Support
Barcode	1D UPC-A/UPC-E/JAN13(EAN13)/JAN8 (EAN8)/CODE39/ITF/CODABAR/ CODE93/CODE128 2D PDF417, QR code
Detection	Sensors"Lack of paper detection, open cover detection, overtemperature detection
Power Supply	InputAC 100V-240V 50/60HZ OutputDC 24V/2.5A
Paper	
Paper Type	Thermal Receipt Paper
Paper Width	58mm (57.5 ± 0.5mm)80mm (79.5 ±0.5mm)
Paper Thickness	0.04~0.08mm
Roll Dia	Max. 82 mm
Paper Load	Easy paper loading
Paper Cut	Auto-cutter(half cut)
Physical Characteristics	
Working Condition	5°C~45°C, 10%~90%RH
Storage Condition	-20°C-60°C,10%~90%RH
Dimensions	137(D)x137(W)x130(H)mm
Colour	Black
Net weight	1kg
Gross weight	1.7kg
Reliability	
Printer mechanism	life15 million lines
Printing head	150KM
cutter	2million
MTBF	360,000H
MCBF	60 million lines
Accessories	Data cable, Power adaptor, Power cord, Paper roller fixer, Paper roller, CD, Manual, Paper separator
Packing	
Individual boxDimension	230X155X144mm(LXWXH) 1unit/carton
Master cartonDimension	470X460X325mm(LXWXH) 12units/carton
OS	
Emulation	ESC/POS
Driver	Windows XP /Vista/ Win7/Win8 /Win10/Win11/Win 2000/WinCE/OPOS/JPOS
SDK	Android, iOS

