

Model number	Z58-III		
Print	Printing Mode	Direct Thermal	
	Print Speed	90mm/s	
	Resolution	384dots/line	
	Print Width	48mm	
	Interface	USB/USB+WIFI/USB+BT	
Memory	Input Buffer	256 kilobytes	
	Flash	256 kilobytes	
Font	Font A	12x24	
	Font B	9x17	
	Chinese	GB18030,BIG5 24x24dots	
Barcode	1D	UPC-A/UPC-E/JAN13 (EAN13) /JAN8 (EAN8) /CODE39/ITF/CODABAR/CODE93/CODE128	
Power Supply	Input	AC 100V-240V 50/60HZ	
	Output	DC 12V/2.5A	
Money Box	DC 12V/1A		
Paper	Paper Type	Heat-sensitive paper	
	Paper Width	58mm	
	Paper Thickness	0.06~0.08mm	
	Diameter	Max. Ø 48 mm	
	Paper Load	Easy paper loading	
	Paper Cut	Manual tear	
Physical Properties	Work Environment	0° C~45° C, 10%~80%RH	
	Storage Environment	-10° C-60° C,10%~90%RH	
	Dimension	100(D)x100(W)x75(H)mm	
	Net Weight	0.3kg	Gross Weight
Life Span	Print Head	50KM	
	Cutter	There is NO	
Accessories	Data Selection, Adapter, Power Cord, Paper Roll, CD, Manual		
Packing	Individual Box	18.4*16.4*13.5CM(LXWXH)	1unit/carton
	Master Carton	52*39.5*43.8CM(LXWXH)	18units/carton
Operating System	Emulation	ESC/POS	
	Driver	Windows XP /Vista/ Win7/Win8 /Win10/Win 2000/Win	
	SDK	Android, IOS	