



Model		ZY302		
Printing	Print Method	Direct Thermal		
	Print Speed	200mm/s		
	Resolution	576dots/line or 572dots/line		
	Printing Width	72mm		
	Paper separator(option)	48mm/52mm/56mm/64mm/68mm/76mm/80mm		
	Interface	RS232C+USB		
Kitchen function	Power,Paper,Error Alerts	Support		
	LED light with	Without		
	Hanging device	Equipped		
Memory	Input buffer	256kbyte		
	NV Flash	256kbytes		
Fonts	Font A	12x24		
	Font B	9x17		
Fonts	Chinese	GB18030,BIG5 24x24dots		
	Japanese/Korea	Support		
	User-defined	Support		
Barcode	1D	UPC-A/UPC-E/JAN13 (EAN13) /JAN8 (EAN8) /CODE39/ITF/CODABAR/CODE93/CODE128		
Detection	Sensors	Paper out, cover open, cutter jam,paper jam		
Power Supply	Input	AC 100V-240V 50/60HZ		
	Output	DC 24V/2.5A		
Paper	Paper Type	Thermal Receipt Paper		
	Paper	48mm/52mm/56mm/64mm/68mm/76mm/80mm		
	Paper Thickness	0.06~0.08mm		
	Roll Dia	Max. Ø 83 mm		
	Paper Load	Easy paper loading		
	Paper Cut	Manual tear & Auto-cutter		
Physical Characteristics	Working Condition	0° C~45° C, 10%~80%RH		
	Storage Condition	-10° C-60° C,10%~90%RH		
	Dimensions	191(D)x146(W)x12.9(H)mm		
	Net weight	1.84kg	Gross weight	2.04kg
Reliability	Printing head	150KM		
	cutter	1.5million		
Accessories	data cable,power adaptor,power code,paper roller,CD>manual,paper separator(option)			
Packing	Individual box	Dimension 25X20X16cm(LXWXH)	1unit/carton	
	Master carton	Dimension 64X28X37cm(LXWXH)	6units/carton	
OS	Emulation	ESC/POS		
	Driver	Windows XP /Vista/ Win7/Win8 /Win10/Win 2000/Win CE/OPOS/JPOS		
	SDK	Android, IOS		