

Model number		ZY606		
print	Printing mode	Direct thermal		
	Printing speed	260mm/s		
	Resolution	576 points/line or 572 points/line		
	Print width	72mm		
	Paper separator(option)	48mm/52mm/56mm/64mm/68mm/76mm/80mm		
	Interface	Serial port +USB+ network port/Serial port +USB+ network port +WIFI/ serial port +USB+ network port + Bluetooth		
	Page mode	support		
Kitchen function	Power, Paper, Erro	support		
	LED flashing tip	support		
	Hanging device	support		
Memory	Input buffer	256kbytes		
	NV Flash	256kbytes		
Fonts	Font A	12x24		
	Font B	9x17		
	Chinese	GB18030,BIG5 24x24dots		
	Japanese/Korean	support		
	User-defined	support		
Barcode	1D	UPC-A/UPC-E/JAN13 (EAN13) /JAN8 (EAN8) /CODE39/ITF/CODABAR/CODE93/CODE128		
	2D	QR code		
Sensors		Lack of paper, paper jam, black calibration position (optional)		
Power supply	Input	AC 100V-240V 50/60HZ		
	output	DC 24V/2.5A		
Paper	Paper Type	Heat-sensitive paper		
	Paper Width	48mm/52mm/56mm/64mm/68mm/76mm/80mm		
	Paper Thickness	0.06~0.08mm		
	Roll Dia	Max. Ø 83 mm		
	Paper Load	Easy paper loading		
	Paper Cut	Manual tear or Auto-cutter		
Physical Characteristics	Working Condition	0°C~45°C, 10%~80%RH		
	Storage Condition	-10°C-60°C,10%~90%RH		
	Dimensions	184(D)x143(W)x148(H)mm		
	Net weight	1.94kg	Gross weight	2.14kg
Reliability	Printing head	150 km		
	cutter	1.5million		
Accessories		Data Cable, Adapter, Power cord, paper Roll, CD, Manual, Shelf Baffle (Optional)		
Packing	Individual box	Dimension 26X21X17cm(LXWXH)	1unit/carton	
	Master carton	Dimension 64X28X36cm(LXWXH)	6units/carton	
OS	Emulation	ESC/POS		
	Driver	Windows XP /Vista/ Win7/Win8 /Win10/Win 2000/Win CE/OPOS/JPOS		
	SDK	Android, IOS		

