

Model		ZY910	
Print	Printing Mode	Direct Thermal	
	Fastest Printing Speed	152mm（6"）/s MAX	
	Resolution	203dpi	
	Maximum Print Width	108mm（4.25"）	
	Maximum Print Length	1778mm（77"）	
	Interface	Standard: USB Optional: USB+ network port /USB+ serial port + network port + Bluetooth /USB+ serial port + network port +wifi/USB+ Bluetooth /USB+wifi	
Performance Characteristics	Processor	32-bitCPU	
	Memory	8MB Flash Memory/8MB SDRAM	
Character	Font	8 kinds of alphanumeric bitmap, windows fonts can be downloaded by software	
Bar Code	1D	CODE39, CODE93, CODE128UCC, CODE128, SUBSETS A, B, C, CODABAR, INTERLEAVED 2 of 5,EAN-8,EAN-13,EAN-128,UPC-A,UPC-E,EANandUPC2(5)DIGITS ADD-ON,MSI,PLESSEY,POSTNET,China POST	
	2D	PDF-417,Maxicode,DataMatrix,QR code	
Power Supply	Input	Ac 100v to 240v 50/60 Hz	
	Output	Dc 24 v, 2.5, 60 w	
Printer Paper	Paper Type	Heat-sensitive paper	
	Maximum Label Width	118mm	
	Paper Thickness	0.06~0.25mm	
	Roll Diameter	25.4~76.2mm（1"~3"）	
	Label Length	10~1778mm（0.39"~70"）	
	Label Roll Capacity	127mm（5"）(external diameter)	
Physical Characteristics	Working Environment	Temperature: 5° C to 40° C, humidity: 25% to 85%RH	
	Storage Environment	Temperature: -40° C to 60° C, humidity: 10% to 90%RH	
	Dimension	226.5(D)x183(W)x162.5(H)mm	
	Weight	1.3KG	
Reliability	Warranty Period	12months	
	Print Head Life	30km	
Attachment	Data Cable, Power Adapter, Power Cord, Paper Roll, CD, Manual, Shelf Baffle (Optional)		
Package	Inner box	26.6X16.4X16cm(LXWXH)	1 piece/box
	Outer box	55X35X51.5cm(LXWXH)	12 pieces/box
OS	Virtual Instruction	TSPL、EPL	
	Driver	Windows/Linux/Mac	
	SDK	Windows/Android/ios	