FL2C Flood Light Datasheet







Key Features

⇒ Efficacy: 170 lm/w ⇒ LED Chip: SMD3030

⇒ SDCM: <5

⇒ **Beam Angle:** 30° | 60° | 90° | 30° x 90° | 80° x 140°

⇒ Control: 0-10V | DALI | DMX512


⇒ IP Rating: IP66⇒ Installation: Bracket⇒ Warranty: 5 years

Application


Sports venues; Plazas and parks; Construction sites; Building facades; Parking lots and storage areas; Ports and docks; Industrial plants; Emergency and disaster relief sites; Billboards and large signs; Airports (auxiliary lighting), etc.

Photometry


30°(PC lens)




60°(PC lens)




90°(PC lens)



30°x90°(PC lens)









FL2C Flood Light Datasheet

Product Data

| Model No. | FL2C-150 | | | | | |
|------------------------|-------------------------------|--|--|--|--|--|
| Power | 150W | | | | | |
| Lumen Output | 25,500lm | | | | | |
| Luminous Efficacy | 170 lm/w | | | | | |
| ССТ | 3000К 4000К 5700К 6500К | | | | | |
| CRI | Ra≥70 (Ra≥80 optional) | | | | | |
| Input Voltage | 100-277 VAC; 50Hz 60Hz | | | | | |
| Housing Color | Gray | | | | | |
| Housing Material | Aluminum, PC | | | | | |
| IP Rating | IP66 | | | | | |
| Operating temperatu re | -30°C to +50°C | | | | | |
| Operating humidity | 10% to 90% RH | | | | | |
| Lifespan | 100,000 hours | | | | | |
| Warranty | 5 years | | | | | |

ErP Technical Specification (25°C operating temperature)

| Item | Specification & Data | | |
|--------------------------------------|----------------------|--|--|
| Efficiency In | ≥92% | | |
| Power Factor | PF≥0.95 | | |
| Energy Efficiency Class | С | | |
| Standard Deviation of Color Matching | <5 | | |
| Starting Time | <0.2S | | |
| Warm-up Time to 60% | <0.5S | | |
| Lumen Maintenance at e.o.l. | >70% | | |
| Lifetime | L70/B10@100,000hours | | |

Note: 1. The above parameters are all obtained at +25°C and there are errors within the allowable range of relevant standards.

2. This specification book is for reference only. We retains the right to optimize and modify without pre -notification!



FL2C Flood Light Datasheet

Packaging

| Model No. | PCS/CTN | N.W | G.W | Volumetric Weight | Carton Size and Volume | 20GP(28m³) | 40HC/HQ(68m³) |
|-----------|---------|--------|--------|----------------------|---|------------|---------------|
| FL2C-150 | 1 | 2.9 kg | 3.5 kg | 1.8 kg | L392xW353xH66 mm ≈ 0.009 m ³ | 3,111 CTNS | 7,555 CTNS |

Dimension (unit: mm)

