

IshHOP-E801 Thermal Receipt Printer



Product description:

HOP-E801 is a high quality HOIN brand thermal printer which designed for network and kitchen printing. 300MM/S(Max) high speed printing; excellent waterproof, oil proof, dust proof structure design; rich interface options including USB,LAN,COM,Bluetooth,WIFI. Real-time monitoring function and large input buffer can avoid bills losing. Leading technology with high performance make sure a high-quality, worry free printing experience.

Product performance:

- •300 mm / second(Max) ultra high-speed printing, improve the printing efficiency;
- Excellent waterproof, anti oil, anti-dust structure design;
- •Support wall hanging function, meet the special environment printing;
- •Movable baffle design, support 80MM, 58MM different width of the paper roll printing;
- Support 80MM large diameter roll;
- Support kitchen printing and Internet printing;
- Support printer monitoring function, to avoid losing bills;
- •Using 100M Ethernet card, connect printer faster, to avoid losing bills;
- Recover printing after network disconnection, to avoid losing bills;
- 2048K super input buffer,to avoid losing bills;
- Support LOGO Graphical download and print;
- Support 1D,2D bar code printing;
- Support order come remind and error alarm;
- Support re-print;
- •GB18030 Large font;



- Support Multi language printing;
- •Rich Interface:

USB, USB+Internet, Internet+USB+COM, Internet+USB+WIFI, USB+Bluetooth, USB+WIFI, USB+LAN+COM+Bluetooth+WIFI

- •Compatible with ESC/POS print instruction mode;
- Support Windows, Linux, Android and IOS system;

Application:

Shopping malls, restaurants, stores, warehousing, taxation, banking, medical, postal

Printer Parameters:

Item		Parameters
	Printing	Thermal Line
	Method	
	Printing width	72mm
Print	Resolution	576 Dots/Line or 512 Dots/Line (8dots/mm, 203dpi)
parameters	Print speed	300mm/Second
	Interface	USB,USB+LAN,USB+LAN+COM,USB+Bluetooth,USB+WIFI,
		USB+LAN+WIFI,USB+LAN+COM+Bluetooth+Wifi
	Line Spacing	3.75mm(Can adjust line spacing by command)
	Line No.	FontA-48Lines/FontB-64Lines/Simple,traditional Chinese-24
		lines
	Character	standard GB18030 simplified / traditional Chinese Fonts
	Character	ANK character,Font A: 1.5×3.0mm(12×24 dots)
	Size	Font B: 1.1×2.1mm (9×17 dots) Simplified/Traditional
		Chinese: 3.0×3.0mm(24×24 dots)
	Extended	PC437/Katakana/PC850/PC860/PC863/PC865/WestEurope/G
	character set	reek/Hebrew/EastEurope/Iran/WPC1252/PC866/PC852/PC85
		8/IranII/Latvian/Arabic/PT151,1251/PC737/WPC/1257/ThaiVie
		tnam/PC864/PC1001/(Latvian)/(PC1001)/(PT151,1251)/(WPC
Bar code		1257)/(PC864)/(Vietnam)/(Thai)
Character	Bar code	1D bar code:
		UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)CODE39/ITF/CO
		DABAR/CODE93/CODE128
		2D barcode: QRCODE
Graphics	Graphics	Supports bitmap download and print
printing	printing	
Cutter	Cutter	Full cut/Half cut
	Function	
Paper	Туре	Thermal
	Width	79.5±0.5mm
	Diameter	≤80mm



HOIN 深圳市弘印电子科技有限公司 Shenzhen Hoin Electronic Technology Co.,Ltd

	Feed method	Easy feed(Clameshell feed)
Print	Commands	ESC/POS
commands		
Power	Power	Input: AC 100V-240V,50-60Hz
	Adaptor	Output: DC 24V/2.5A
	Cash Drawer	DC 24V/1A
	output	
Buffer	Input Buffer	2048K bytes
	NV Flash	256K bytes
physical	Weight	1.15KG
characterist	Dimension	186*145*135
ics		
environme	Working	Temp: 5 ~ 45°C, Humidity: 10 ~ 80%
nt	Storage	Temp: -10 ~ 50°C ,Humidity: 10 ~ 90%(No dew)
Reliability	Print Head	100KM (print density≤12.5)
parameter	Life	
	Cutter Life	1000,000times
Software	Driver	Android,IOS,Linux,,Windows