

HOP-E58 Thermal Receipt Printer



Product description:

HOP-E58 is a 58mm desk thermal printer, the exquisite and fashion design, small and smart, full of high technology sense. Using large motor and a big gear movement design, support 83MM large diameter roll and 130 mm / s high speed printing, giving perfect solution to solve the problem of small diameter roll and low speed in other 58mm printer, making printing more efficient. It provides a rich interface:USB, network port (100M), WIFI, Bluetooth optional, enable print more flexible and convenient.

Product performance:

- Appearance compact design, fashion technology;
- Easy paper feed structure, simple and convenient operation;
- •High reliability of large motor and large gear movement;
- •130 mm / second ultra high speed print, significantly improve the printing efficiency;
- •Big paper warehouse design, the perfect support for 83MM large diameter rolls;
- •Rich interface optional: USB, COM, Internet (100M), WIFI, Bluetooth;
- •Support GB18030 large font and multi language;
- Supports LOGO and graphics downloads and print;
- Supports Windows, Linux, Android and IOS system;
- •100M Ethernet interface, print quickly while avoiding losing bills.

Application:

Shopping malls, restaurants, stores, warehousing, taxation, banking, medical, postal



HOIN 深圳市弘印电子科技有限公司 Shenzhen Hoin Electronic Technology Co.,Ltd

Printer Parameters:

Items		Parameters
	Printing	Thermal Line
	Method	
	Printing	48MM
	Method	
	Resolution	384dots/Line (8dots/mm, 203dpi)
Print	Printing	130mm/Second
parameters	Speed	
	Interface	USB, USB+COM, Internet (100M), USB+WIFI, USB+Bluetooth
	Type	
	Line	3.75 mm (Can adjust line spacing by command)
	Spacing	
	Line No.	Font A:32 character /Line
		Font B:42 character/Line
		Simple, traditional Chinese-16 lines
	Character	Standard GB18030 simplified / traditional Chinese Fonts
	Character	ANKcharacter , Font A: 1.5×3.0 mm (12×24 点)
	Size	Font B: 1.1×2.1 mm (9×17 点) Simplified/Traditional
		Chinese: $3.0 \times 3.0 \text{mm} (24 \times 24 \text{ Dots})$
Bar code	Extended	PC437/Katakana/PC850/PC860/PC863/PC865/WestEurope/Gree
Character	character	k/Hebrew/EastEurope/Iran/WPC1252/PC866/PC852/PC858/Ira
	set	nII/Latvian/Arabic/PT151,1251/PC737/WPC/1257/ThaiVietn
		am/PC864/PC1001/(Latvian)/(PC1001)/(PT151,1251)/(WPC12
		57)/(PC864)/(Vietnam)/(Thai)
	Bar code	1D bar code:
		UPC-A/UPC-E/JAN13 (EAN13)/JAN8 (EAN8) CODE39/ITF/
		CODABAR/CODE93/CODE128
		2D bar code: QRCODE
Graphics	Graphics	Supports bitmap download and print
printing	printing	
Paper	Type	Thermal Roll
	Width	57.5 ± 0.5 mm
	Diameter	≤83mm
	Feed Method	Easy feed (Clameshell feed)
Print	Commands	ESC/POS
commands	 	T
Power	Power	Input: AC 100V-240V, 50-60Hz
	Adaptor	Output: DC 12V/2A
	Casher	DC 12V/1A
	Drawer	
	output	



HOIN 深圳市弘印电子科技有限公司 Shenzhen Hoin Electronic Technology Co.,Ltd

Buffer	Input	4K
	Buffer	
	NV Flash	40K
physical	Weight	750g
characteris	Dimension	180*115*127 (MM)
tics		
Environment	Working	Temp: 5 ~ 45°C, Humidity: 10 ~ 80%
	Storage	Temp: -10 ~ 50°C , Humidity: 10 ~ 90% (No dew)
Reliability	Print Head	50KM (print density≤12.5)
parameter	Life	
Software	Driver	Android, IOS, Linux, , Windows