

HOP-HQ480B

4 Inch Thermal Label and Receipt Printer (Dual Mode)



Specifications

Items	Parameters/ Descriptions
User Indicator	A power switch,A feed button,A LED indicator (Multi-color)
Sensor	Gap sensor Black mark sensor (the sensor position moves along with the black mark) Printer head up sensor Temperature sensor (THP)

Paper Type	Label Paper	Width	37-123 mm
		Height	10-280mm
		Diameter	25-120mm
		Media Type	Continuous, gap, black mark, fan-fold, punched hole, label paper, tag paper card
		Thickness	0.05mm-0.26mm
		Printing width(Max)	108mm
	Receipt Paper	Width	58mm,80mm,104mm
		Diameter	80mm(Max)
Label Paper Type		Roll type or Stack type	
Printer Size		240 mm (L) x 190 mm (W) x 170 mm (H)	
Printer Weight		1.55kg (Pure printer weight without package)	
Open Method		Shell way	
Print Method		Direct thermal	
Print Location		Center printing	
Resolution		203 dpi	
Print Density		1-15 density Level	
Speed		152mm/s(max)	
Memory		512KB Flash Memory/320KBRAM+ 2MB PSRAM	
Interface		USB/Ethernet/COM/Bluetooth/Wi-Fi Optional	
1D Barcode		1D barcode: Code 39, Code 93, Code 128UCC, Code 128 subsets A, B, C, Codabar, Interleaved 2 of 5, EAN-8, EAN-13, EAN-128, UPC-A, UPC-E, EAN and UPC 2(5) digits add-on	
2D BarCode		2D barcode: PDF-417, QR code	
Rotation		0°, 90°, 180°, 270°	
Emulation		TSPL, CPCL, ESC/POS	
System		Windows,Android,iOS,Mac,Linux	
TPH Working Life		Over 100,000,000 pulses or over 50 km	
Power Adaptor		Input: AC 100V~240V (50Hz/60Hz) Output: DC 24V  2.5A	
Using Environment	working altitude	Only suitable for safe use in areas below 2000m above sea level	
	working	5℃~50℃ (non-condensing)	
	storage	-20℃~60℃ (non-condensing)	
	Working humidity	20%~85% RH (non-condensing)	
	Storage humidity	5%~95% RH (non-condensing)	