

HOP-HQ300

3 Inch Portable Thermal Label and Receipt Printer(Dual Mode)



Features:

- Support both label and receipt printing
- Command: TSPL, CPCL, ESC/POS
- 2500mah lithium polymer battery
- Resolution: 203DPI
- 0.96 inch LED Screen

Parameters:

Items			Parameters/Descriptions
User Indicator			Power Button, Feed button, Setting button, OLED Screen
Sensor			Gap sensor, Black mark sensor, Temperature Sensor (THP)
Paper Type	Label Paper	Width	20mm-80mm
		Diameter	50mm(Max)
		Height	10-185mm
		Media Type	Continuous, gap, black mark
		Thickness	0.05mm-0.26mm
		Printing Width	72mm(Max)
	Receipt	Width	80mm

		Diameter	<50mm
Label Paper Type		Roll type	
Printer Size		115 mm (D) x111 mm (W) x60 mm (H)	
Printer Weight		364g (Pure printer weight without package)	
Open Method		Shell way	
Print Method		Direct thermal	
Resolution		203 dpi	
Print Density		1-15 density Level	
Speed		70mm/sec(Max)	
Memory		512KB Flash Memory/320KBRAM	
Interface		USB and Bluetooth	
1D Barcode		Code 39, Code 93, Code 128UCC, Code 128 subsets A, B, C, Codabar, Interleaved 2 of 5, EAN-8, EAN-13, EAN-128, UPC-A, UPC-E, EAN and UPC 2(5) digits add-on	
2D BarCode		QR code	
Rotation		0°,90°,180°,270°	
Emulation		TSPL, CPCL, ESC/POS	
Driver		Windows,Android,iOS, Mac, Linux;	
TPH Working Life		Over 100,000,000 pulses or over 50 km	
Power Adaptor		Input: AC 100V~240V(50Hz/60Hz) Output: DC 5V  1000mA	
Battery	Type	Rechargeable Lithium polymer battery	
	Capacity	2500mAh/7.4V	
	Charger	5.0V DC,1A	
working altitude		Only suitable for safe use in areas below 2000m above sea level	
working environment		5℃~50℃(non-condensing)	
storage environment		-20℃~60℃(non-condensing)	
Working humidity		20%~85% RH(non-condensing)	
Storage humidity		5%~95% RH(non-condensing)	