

HOP-Q200 Mini Portable Thermal Receipt Printer



Application:

Warehousing, transportation, logistics, supermarket, tobacco, hydro-power reading, mobile government affairs, mobile police, postal and other industries

Parameters:

Item		Parameter
Print parameter	Printing Method	Thermal Line
	Effective Printing Width	48mm
	Resolution	384 dots/line (8dots/mm, 203dpi)
	Printing Speed	70 mm/s(Max)
	Interface	USB+Bluetooth
	Line spacing	3.75mm (Can adjust line spacing by command)
	Line No.	Font A:32 character /Line Font B:42 character/Line
Bar code character	Character Size	ANK character, Font A: 1.5×3.0mm (12×24 dots) Font B: 1.1×2.1mm (9×17 dots)
	Extended character set	PC437/Katakana/PC850/PC860/PC863/PC865/West Europe/Greek/Hebrew/East Europe/Iran/WPC1252/PC866/PC852/PC858/Iran II/Latvian/Arabic/PT151,1251/PC737/WPC/1257/Thai Vietnam/PC864/PC1001/(Latvian)/(PC1001)/(PT151,1251)/(WPC 1257)/(PC864)/(Vietnam)/(Thai)
	Bar code	1D.Bar code: UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)CODE39/ITF/ CODABAR/CODE93/CODE128 2D.Bar code: QRCODE

Graphics printing	Graphics printing	Supports bitmap download and print (support each bitmap size max. 24K bytes, download up to 5pcs)
Power saving Mode	Smart power saving	Support
	Consumption	Support
	Dormancy	Support
Indicator	Power Display	Support
	Charge Indicator	Support
	Lack of paper	Support
Paper	Type	Thermal
	Width	57.5±0.5mm
	thickness	≤0.12mm
	Diameter	≤40mm
	Feed	Easy (Clamshell feed)
Print commands	Commands	ESC/POS
Power	Type	Rechargeable lithium polymer battery
	Capacity	2000mAh/7.4V
	Charger	5.0V/1A
Buffer	Input	4KB
	NV Flash	120KB
Physical features	Weight	240g (Pure printer weight without package)
	Dimension	120*81*58(MM)
Environment	Operating	Temp: 5 ~ 45℃, Humidity: 10 ~ 80%
	Storage	Temp: -10 ~ 50℃, Humidity: 10 ~ 90% (No Dew)
Reliability	Print head life	50KM (Printing Density≤12.5)
System	Android,iOS,Linux,Windows	