

HOP-H200 Mini Portable Thermal Receipt Printer



Product description:

HOP-H200 is a newly designed mobile receipt printer with high-performance. Smooth modeling with ergonomic design and excellent grip for easy hand-taking. Support USB fast charging; Support printer working and charging at the same time, greatly improve the efficiency of the printer; Large capacity polymer lithium-ion battery to ensure a long printing time; Simple and practical human-printer interaction promote for the real perfect practical using of the printer.

Products Features:

- •Flowing and graceful model with ergonomic design and excellent grip for a easy hand-taking
- Support 1D,2D barcode printing;
- •While compatible with Windows, Linux, Android and iOS systems;
- •Super battery life, with smart power saving and power consumption control functions , to ensure longer print time;
 - •Rich Interface optional: USB/USB+Bluetooth/USB+WiFi/USB+Bluetooth+Wi-Fi;
 - Support USB fast charging and realize printing while charging, which can greatly provide printing efficiency;
 - Anti fall of 1.5M cement floor;

Application:

Warehousing, transportation, logistics, supermarket, tobacco, hydro-power reading, mobile government affairs, mobile police,postal and other industries



Parameters:

| Item | | Parameter |
|-------------------|--------------------|--|
| Print parameter | Printing Method | Thermal Line |
| | Effective Printing | 48mm |
| | Width | |
| | Resolution | 384 dots/line (8dots/mm, 203dpi) |
| | Printing Speed | 90 mm/s(Max) |
| | Interface | USB+Bluetooth(Wi-Fi Optional) |
| | Line spacing | 3.75mm(Can adjust line spacing by command) |
| | Line No. | Font A:32 character /Line |
| | | Font B:42 character/Line |
| | Character Size | ANK character, Font A: 1.5×3.0mm(12×24 dots) |
| | | Font B: 1.1×2.1mm (9×17 dots) |
| | Extended character | PC437/Katakana/PC850/PC860/PC863/PC865/WestEurope/Gre |
| | set | ek/Hebrew/EastEurope/Iran/WPC1252/PC866/PC852/PC858/Ira |
| | | nII/Latvian/Arabic/PT151,1251/PC737/WPC/1257/ThaiVietnam/P |
| | | C864/PC1001/(Latvian)/(PC1001)/(PT151,1251)/(WPC1257)/(PC |
| Bar code | | 864)/(Vietnam)/(Thai) |
| character | Bar code | 1D.Bar code: |
| | | UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)CODE39/ITF/ |
| | | CODABAR/CODE93/CODE128 |
| | | 2D.Bar code: QRCODE |
| Graphics printing | Graphics printing | Supports bitmap download and print (support each bitmap size |
| | | max. 16K bytes, download up to 5pcs) |
| | Smart power saving | Support |
| Power saving | Consumption | Support |
| Mode | Dormancy | Support |
| | Power Display | Support |
| Indicator | Charge Indicator | Support |
| | Lack of paper | Support |
| Paper | Туре | Thermal |
| | Width | 57.5±0.5mm |
| | thickness | ≤0.12mm |
| | Diameter | ≤40mm |
| | Feed | Easy (Clamshell feed) |
| Print commands | Commands | ESC/POS |
| Power | Туре | Rechargeable lithium polymer battery |
| | Capacity | 1500mAh/7.4V |
| | Charger | 5.0V/1A |



| | Input | 4KB |
|-------------------|---------------------------|---|
| Buffer | NV Flash | 80KB |
| Physical features | Weight | 176g (Pure printer weight without package) |
| | Dimension | 112*79*48(MM) |
| | Operating | Temp: 5 ~ 45 ℃, Humidity: 10 ~ 80% |
| Environment | Storage | Temp: $-10 \sim 50^{\circ}$, Humidity: $10 \sim 90\%$ (No Dew) |
| Reliability | Print head life | 50KM (Printing Density≤12.5) |
| System | Android,iOS,Linux,Windows | |