

HOP-E300 80mm Mini Portable Thermal Receipt Printer



Products Features:

- Business style design, more fashion
- Support 1.D,2.D bar code printing
- While compatible with Windows, Linux, Android and iOS systems
- Big paper warehouse design,support 40mm Diam.paper rolls,to avoid change paper frequently
- With 2500mAh rechargeable lithium polymer battery,super battery lasting time, with smart power saving and power consumption control functions , to ensure longer print time
- Support USB,Bluetooth,Wi-Fi communications
- Special power remaining indicator light, to control the printer power at any time
- Support sound and light reminder when lack of paper or printing abnormal
- Support small font printing,to achieve more printing choice
- Anti fall of 1.5M cement floor

Application:

Warehousing, transportation, logistics, supermarket, tobacco, hydro power reading, mobile government affairs, mobile police, postal and other industries

Parameters :

Item		Parameter
Print parameter	Printing Method	Thermal Line
	Effective Printing Width	72mm
	Resolution	576 dots/line (8dots/mm, 203dpi)
	Printing Speed	90mm/s (Max)
	Interface	USB+Bluetooth, USB+Bluetooth+Wi-Fi, (RS232 Optional)
	Line spacing	3.75mm (Can adjust line spacing by command)
	Line No.	Font A:48 character /Line Font B:64 character/Line Simple, traditional Chinese-24 lines
	Character	The standard GB18030 simplified / traditional Chinese characters library
	Character Size	ANK character, Font A: 1.5×3.0mm (12×24 dots) Font B: 1.1×2.1mm (9×17 dots) Simplified/Traditional: 3.0×3.0mm(24×24dots)
Bar code character	Extended character set	PC437/Katakana/PC850/PC860/PC863/PC865/West Europe/Greek/Hebrew/East Europe/Iran/WPC1252/PC866/PC852/PC858/Iran II/Latvian/Arabic/PT151,1251/PC737/WPC/1257/Thai Vietnam/PC864/PC1001/(Latvian)/(PC1001)/(PT151,1251)/(WPC1257)/(PC864)/(Vietnam)/(Thai)
	Bar code	1D.Bar code: UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)CODE39/ITF/ CODABAR/CODE93/CODE128 2D.Bar code: QR CODE
Graphics printing	Graphics printing	Supports bitmap download and print (support each bitmap size max. 24K bytes, download up to 5pcs)
Power saving Mode	Smart power saving	Support
	Consumption	Support
	Dormancy	Support

Indicator	Power Display	Support
	Charge Indicator	Support
	Lack of paper	Support
	Beep	Lack of paper,printing abnormal alarm
Paper	Type	Thermal
	Width	79.5±0.5mm
	thickness	≤0.12mm
	Diameter	≤40mm
	Feed	Easy (Clamshell feed)
Print commands	Commands	ESC/POS
Power	Type	Rechargeable Lithium polymer battery
	Capacity	2500mAh/7.4V, can be charged more than 800 times sustainable printing 150 meters or 4 hours under normal use
	Charger	9.0V/1A
Buffer	Input	4KB
	NV Flash	120KB
Physical features	Weight	291g
	Dimension	114*103*50(MM)
Environment	Operating	Temp: 5 ~ 45℃, Humidity: 10 ~ 80%
	Storage	Temp: -10 ~ 50℃ , Humidity: 10 ~ 90% (No Dew)
Reliability	Print head life	50KM (Printing Density≤12.5)
System	Android,iOS,Linux,Windows	