NSPV
NewSun PV Technology Co.,Ltd

ROOF PIPE FLASHING

Product description:

A pyramid fast suture of silicone waterproof cover is designed for waterproofing roof design, particularly suitable for all kinds of round tubular seepage control requirements, but before installation must according to the tube diameter cutting to the appropriate size.

Product technical parameters

Materials: silicone

Color: Black / Red / Gray

Rim: Aluminum

Thickness: 1.5-2.0mm

Warranty: 25 Year

Base Size	Apply pipe size
mm	mm or inch
100x100mm	0-35mm or 0-1½″
200x200mm	50-100mm or 2-4″
310x310mm	100-200mm or 4-8″

Product advantage

- Convenient installation
- Suitable for any shape of the roof
- Can withstand the extreme temperature -50° C to 150° C
- More effective waterproof measures
- Do not produce wrinkles, no leakage hidden trouble
- Product appearance concise
- Twenty-five Year warranty

25 YEAR WARRANTY

Installation Instructions:



- Trim the cone to suit pipe size using sharp tin snips.



- Slide NSPV flashing down over pipe. Lubricating the pipe with water allows the pipe to slide snuggly into position.



- Apply a neutral-cure silicone sealant by turning back the flexible flange.



- Press base to the roof profile by hand, smooth out any awkward creases. Don't fully extend to allow for vibration.



- Fasten using self drilling washered screws. Fit fasteners progressively outward in opposing pairs to avoid gaps.



- Finished

