

TROJAN
Discover the Truth of Material

Alpha - 600
Automatic Grinder and Polisher

GRINDING/POLISHING






2024
10 / 11

TROJAN (SUZHOU) MATERIAL TECHNOLOGY CO.,LTD

Alpha-600 Automatic Grinder and Polisher

Alpha-600 is an automatic grinding and polishing machine with compact designed especially for high quality grinding and polishing surfaces needs. The maximum diameter of the grinding dics is as large as 12″(300mm). There are two types of pressurization, central pressure and individual pressure. 4 groups of dosing system are optional. The machine can set & save 20 groups of commonly used grinding programs. It is convenient and quick to obtain high-quality mirror polishing results with high repeatability.



Features:




- Convenient and easy operate on 5.6”touch screen;
- Both central and individual pressure can be achieved;
- Electrical connections for 4 groups of dosing/stirring system;
- Contains 21 groups of commonly used grinding programs ,customized programs also can be saved;
- Large diameter of drain hose;
- Replaceable wheel design makes easy to clean and maintenance;
- The automatic temperature-sensing cooling fan, can reduce failure rate and improve working life;
- Retractable water spout.

Technical Data:


Model		Alpha-600
Head	Force Application	Central and Individual
	Central Force	20-300N
	Individual Force	5-60N
	Power	220V, 400W
	Speed	20-150rpm
	Direction	CCW
Grinder	Power	750W
	Speed	50-750rpm
	Wheel Diameter	8″-10″-12″(203/254/305mm)
	Direction	CW/CCW
Dosing System (optional)	Flow	0-52ml/min
	Amount	4×500ml
Specimen holder	Individual pressure	6xΦ50mm
	Central pressure	6xΦ50mm, 8xΦ40mm, 10xΦ30mm (Customization required)
Operating Environment	Temperature	-20˚C - 60˚C
	Humdity	0-95%RH
Dimension	WxDxH	660×730×640mm
Weight		80kg

Control Panel Introduction:




Home Screen:

1. Procedures selection
2. Automatic mode (Run selected procedure)
3. Manual mode
4. Parameters settings



Automatically mode:


1. Steps of procedure
2. Central or individual force
3. Return to home screen
4. Step selection
5. Raise up or down the polishing head
6. Fill in the dosing hose
7. Overview the grinding parameters
8. Time countdown
9. Run/Stop



Manual mode:

1. Timer
2. Water ON/OFF
3. Dosing bottle selection
4. Switch of dosing system:On/Off/Auto
5. Force setting
6. Items of the polishing head
7. Items of the base grinder
8. Return to the home screen
9. RPM setting
10. Direction of the wheel
11. Force type selection
12. Flush ON/OFF
13. Fill in the dosing hose
14. Raise up/down polishing head
15. Run/Stop


Related Consumables & Accessories:



DiaRe Diamond Disc



Abrasive Paper



Polishing Cloth



Diamond Suspension




Alumina/Silica suspension





Adapter Plate System

Dimension Figure


Unite: mm







Standard Accessories:

1	Working disc		8”（203mm)	1pc
2	Splash ring		Plastic water retaining ring	1pc
3	Circlip		8”（203mm)	1pc
4	Single-point clamping discs and connectors		Φ30 Specimen Holder	1set
5	Inlet pipe		Φ8 PU pipe	1pc
6	Flush pipe		Φ10 PU pipe	1pc
7	Outlet pipe		Corrugated pipe with Φ30mm inner diameter and clamp	1pc
8	Fast connection		DN15mm (for water inlet), Water inlet filter	1set
9	Air inlet pipe		Φ6mm PU pipe	1pc
10	Oily water separator			1pc
11	Abrasive paper		180#(200mm),400#(200mm), 800#(200mm),1200#(200mm), 2500#(200mm)	10 each
12	Magnetic disk		Magnetic disk (200mm)	1pc
13	Adapter		AD-PB (200mm)	1pc
14	Polishing cloth		ET-JP (200mm) YS-JP (200mm)	1 each
15	Power cord		1.5m	1pc

Optional Accessories:

1	Air compressor		220V,1.1kW, Exhaust pressure 0.8MPa, capacity 40L
2	Drip system		500mlx4 group, flow8-52ml/minute
3	Single-point clamping discs and connectors		6xΦ25mm, 6xΦ32mm, 6xΦ40mm, 6xΦ50mm, or other customized
4	Center pressurized clamping disc. Joint head and sample leveling plate		10xΦ30mm, 10xΦ32mm, 8xΦ40mm, 6xΦ50mm, or other customized
5	Working platen and supporting platen		10”（254mm）or 12”（305mm）
6	Circlip		10”（254mm）or 12”（305mm）
7	Magnetic disk		Magnetic disk (250mm or 300mm)
8	Adapter		AD-PB (250mm or 300mm)

Purchase list:

MET-F Metallographic Grinding Foil：

FEPA(Grit)	8in (200mm)	10in (250mm)	12in (300mm)	Package
120	03.18.110	03.18.210	03.18.310	100pcs
180	03.18.120	03.18.220	03.18.320	100pcs
240	03.18.130	03.18.230	03.18.330	100pcs
320	03.18.140	03.18.240	03.18.340	100pcs
400	03.18.150	03.18.250	03.18.350	100pcs
600	03.18.160	03.18.260	03.18.360	100pcs
1200	03.18.170	03.18.270	03.18.370	100pcs

Silicon Carbide Abrasive Paper：

FEPA(Grit)	8in PSA (200mm)	10in PSA (250mm)	12in PSA (300mm)	8in Plain Back (200mm)	10in Plain Back (250mm)	12in Plain Back (300mm)	Package
120	03.04.203	03.04.503	03.04.803	03.03.103	03.03.403	03.03.703	50pcs
180	03.04.204	03.04.504	03.04.804	03.03.104	03.03.404	03.03.704	100pcs
400	03.04.207	03.04.507	03.04.807	03.03.107	03.03.407	03.03.707	100pcs
800	03.04.209	03.04.509	03.04.809	03.03.109	03.03.409	03.03.709	100pcs
1200	03.04.211	03.04.511	03.04.811	03.03.111	03.03.411	03.03.711	100pcs
2000	03.04.213	03.04.513	03.04.813	03.03.113	03.03.413	03.03.713	100pcs
2500	03.04.214	03.04.514	03.04.814	03.03.114	03.03.414	03.03.714	100pcs
2400	03.04.215	03.04.515	03.04.815	03.03.115	03.03.415	03.03.715	100pcs
4000	03.04.216	03.04.516	03.04.816	03.03.116	03.03.416	03.03.716	100pcs

Purchase list:

Aluminum Oxide Abrasive Paper:

FEPA(Grit)	8in PSA (200mm)	10in PSA (250mm)	12in PSA (300mm)	8in Plain Back (200mm)	10in Plain Back (250mm)	12in Plain Back (300mm)	Package
60	03.02.401	03.02.500	03.02.801	03.01.101	03.01.401	03.01.701	50pcs
120	03.02.403	03.02.503	03.02.803	03.01.103	03.01.403	03.01.703	100pcs
180	03.02.404	03.02.504	03.02.804	03.01.104	03.01.404	03.01.704	100pcs
240	03.02.404–1	03.02.504–1	03.02.804–1	03.01.104–1	03.01.404–1	03.01.704–1	100pcs
320	03.02.405	03.02.505	03.02.805	03.01.105	03.01.405	03.01.705	100pcs
400	03.02.406	03.02.506	03.02.806	03.01.106	03.01.406	03.01.706	100pcs
800	03.02.408	03.02.508	03.02.808	03.01.108	03.01.408	03.01.708	100pcs
1200	03.02.410	03.02.510	03.02.810	03.01.110	03.01.410	03.01.710	100pcs

DiaNi Electroplated Diamond Grinding Disc:

FEPA(Grit)	8in (200mm)	10in (250mm)	12in (300mm)	Package
80	04.21.110S	04.21.210S	04.21.310S	1PC
120	04.21.120S	04.21.220S	04.21.320S	1PC
200	04.21.125S	04.21.225S	04.21.325S	1PC
400	04.21.130S	04.21.230S	04.21.330S	1PC
800	04.21.140S	04.21.240S	04.21.340S	1PC
1200	04.21.150S	04.21.250S	04.21.350S	1PC

DiaRe Resin–Bonded Diamond Grinding Disc:

FEPA(Grit)	8in (200mm)	10in (250mm)	12in (300mm)	Package
120	04.22.120S	04.22.220S	04.22.320S	1PC
200	04.22.125S	04.22.225S	04.22.325S	1PC
400	04.22.130S	04.22.230S	04.22.330S	1PC
800	04.22.140S	04.22.240S	04.22.340S	1PC
1500	04.22.150S	04.22.250S	04.22.350S	1PC
3000	04.22.160S	04.22.260S	04.22.360S	1PC
5000	04.22.170S	04.22.270S	04.22.370S	1PC

POS/POH Fine Grinding Disc:

Description	8in (200mm)	10in (250mm)	12in (300mm)	14in (350mm)	Package
POS	04.09.110	04.09.115	04.09.120	04.09.125	1pc
POH	04.09.130	04.09.135	04.09.140	04.09.145	1pc

Polishing Cloth:

		8in(200mm)	10in(250mm)	12in(300mm)	Package
Coarse Polishing	NL–CP White Chemical Fiber Polishing Cloth (PSA)	05.06.610	05.06.620	05.06.630	10pcs
	GF–JP White Synthetin Silk Polishing Cloth (PSA)	05.10.010	05.10.020	05.10.030	10pcs
Intermediate Polishing	SC–JP White Silk Polishing Cloth (PSA)	05.05.510	05.05.520	05.05.530	10pcs
	YS–JP White Fiber Polishing Cloth (PSA)	05.07.710	05.07.720	05.07.730	10pcs
	CS–JP Blue Synthetin Silk Polishing Cloth (PSA)	05.12.110	05.12.120	05.12.130	10pcs
	SR–ZP Red Synthetic Fibric Polishing Cloth (PSA)	05.02.150	05.02.160	05.02.170	10pcs
Final Polishing	ET–JP White Synthetic Velvet Polishing Cloth (PSA)	05.03.210	05.03.220	05.03.230	10pcs
	YR–JP Brown Synthetic Rayon Polishing Cloth (PSA)	05.04.310	05.04.320	05.04.330	10pcs
	Final Red Final Precision Polishing Cloth(PSA)	05.13.110	05.13.120	05.13.130	10pcs
	ZN–ZP Black Polyurethane Polishing Cloth (PSA)	05.01.110	05.01.120	05.01.130	10pcs

Adapter System:

	AD–PSA Adapter Disc	AD–Foil Adapter Disc	AD–PB Adapter Disc	Magnetic disc	Package
8in (200mm)	04.08.410	04.08.422	04.08.310	04.08.010	1pc
10in (250mm)	04.08.413	04.08.430	04.08.320	04.08.020	1pc
12in (300mm)	04.08.420	04.08.432	04.08.330	04.08.030	1pc

Purchase list:

Diamond polishing suspension and paste:

Diamond Suspension		Micrometer	Diamond Paste		Diamond Spray
Monocrystalline (500ml)	Polycrystalline (500ml)		Monocrystalline (5g)	Polycrystalline (10g)	Monocrystalline (350ml)
06.01.110-1	06.02.210	0.25um	-	-	-
06.01.120-1	06.02.220	0.5um	-	-	06.03.115
06.01.130-1	06.02.230	1um	06.10.030 (Gray)	06.10.110 (Black)	06.03.320
-	-	2.5um	-	-	06.03.325
06.01.140-1	06.02.240	3um	06.10.040 (Gray)	06.10.130 (Black)	-
-	-	3.5um	-	-	06.03.330
-	-	5um	-	-	06.03.335
06.01.150-1	06.02.250	6um	06.10.050 (Gray)	06.10.160 (Black)	-
06.01.160-1	06.02.260	9um	06.10.060 (Gray)	06.10.190 (Black)	-
-	-	10um	-	-	06.03.340

Precision polishing suspension and polishing powder:

	0.05μm	0.3μm	1μm	Package
AO-W Alumina Polishing Suspension	06.04.210	06.04.220	06.04.230	500ml
AO-P Alumina Polishing Powder	06.13.011	06.13.021	06.13.031	500g
Super Alumina Polishing Suspension	06.04.410/414	-	-	500ml/1.9L
Super Alumina Polishing Powder	06.14.010	06.14.020	-	1LB

Colloidal Silica Polishing Suspension:

SO-T401	SO-A439	SO-A539	Package
06.05.310	06.07.310	06.07.522	500ml
06.05.320	06.07.320	06.07.520	1000ml
06.05.350	06.07.322	06.07.524	1.9L

Polishing lubricants:

PL-W Polishing Lubricant	PL-WB Water-free Blue Low-viscosity Polishing Lubricant	Package
-	06.09.640	500ml
06.09.510	06.09.650	1000ml
06.09.520	06.09.630	5000ml

TROJAN
Discover the Truth of Material

TROJAN (SUZHOU) MATERIAL TECHNOLOGY CO.,LTD
Tel: +86-512-65283666
Email: sales@trojanchina.com
Web: www.trojanworld.com
Add: Building 26,No.228 Gongtang Road,Luzhi Town,Wuzhong Suzhou,China