KosinTec®



High Brightness Menu Board Display

Kosintec's High Brightness Menu Board displays feature a eq ual narro w bezel design, elevating aesthetics while maintaining c larity. Pe rfect for retail product and information displays, they ad opt a hig her-haze panel, reducing reflection and glare for a clear, i mmersiv e viewing experience. With vibrant colors and a slim profi le, they e ffortlessly draw attention in any retail setting.
Versatile and widely applicable, they are ideal for supermarkets, banks, offices, malls, hotels, hospitals, and more.

MU650-MT10

• Optimal Visual Clarity
- High-performance image processor.
- Delivers true color expression and high resolution.
- Offers adjustable picture quality and white balance.

•High-Brightness Display
- Achieves 2000 cd/m² for exceptional brightness.

• Enhanced Component Design
- Lightweight design for easy handling.
- Constructed with high-strength aluminum alloy for durability.
- Modular components facilitate maintenance and replacement.

• Anti-reflection Anti-glare Surface
- Higher haze panel
- Anti-reflection and anti-glare effects.

• Fail Over Support

• GPlay Convenient U disk
- Simply insert the U disk for automatic content copying and playback on the device upon booting

• CMS / Remote Management Support (optional)
- Cloud-based remote management (CetusMSC) and CMS platform (GalaxyASC) support.
- Real-time monitoring of display status, parameters adjustment, and content distribution.
- Remote control via PC and Smart phone.

• Built-in Speaker

• Open API & SDK Support and RS232 Compatible

• Landscape/Portrait Compatible
- Portrait and landscape display orientations.

• OTA Firmware Update
- Enables remote firmware and application updates.
- Designed for seamless upgrades.

• Fire Protection Certification

• Extended Product Warranty
- Engineered for long-term durability.
- Guarantees reliable 24/7 operation.
- Comprehensive warranty ensures customer satisfaction and confidence.

Specification

Hardware Specification

Panel	IPS
Display Size	65 inch
Protection Glass	N/A
Protection Level	/
Front Color	Black
Set Dimension (L*W*D)	1451.8×826.8×58.5mm
Bezel Width Width(mm)	9.5mm
Active Display Area(H*V)	1432.8mm x807.8mm
Resolution	3840 x 2160
Type	60Hz E-LED BLU
Brightness(Typ.)	1200/2000 cd/m²
Contrast Ratio(Typ.)	1300:1
Haze	25%
Viewing Angle(H/V)	178°(H) X 178°(V)(CR≥10)
Chromaticity	16.7M
Color Gamut	72%
Response Time	6ms (Typ)
Operation Hour	24/7
Panel Orientation	Landscape/Portrait
Connectivity	USB2.0*2, HDMI out*1, RJ45*2, Line out*1
Power Input Supply	100-240V AC， 50/60Hz
Power Consumption	300W
Speaker	Built-in mini dual speakers
IR	/
Touch Technology	N/A
Camera	N/A
Installation	Wall mount
VESA Mount	600 x 400mm
Package(W*H*D)	1610 x 200 x 1000mm
Weight (kg)	N.W: 27.1Kg G.W: 36.15Kg
Operating Temperature	-10°C~+50°C
Storage Temperature	-20°C~+60°C

System Specification

CPU	RK3568V
GPU	/
Operating System	Android 11
Cloud Advertising Distribution System	Optional
Cloud Splice System	Optional
Memory	DDR 2G
Storage	EMMC 32GB
Ethernet	Ethernet (RJ45) WiFi 802.11b/g/n 4G LTE(FDD/TDD)(Optional)
Panel Image Rotation	0/90/180/270/360 Angle Rotation
Video Decoder	MPEG-1/2/4,H.264,HEVC,VP8,VP9,AVS+,AVS2.AV1
Audio Decoder	MPEG-1.MPEG-2(layerI/II),MP3,AAC-LC,HE-AAC
Picture Decoding	JPG,JPEG ,PNG ,BMP

What's in the box


Power Cable	x 1 Power cord (based on region)
Remote Control	x 1
Wall Mount Bracket	x 1


Warranty

Warranty	1 year

Dimensions

Unit: mm





* Compatibility may differ by equipment.
* Software compatibility may change over time. Please contact your regional sales representative for details.
* Specifications are subject to change without notice, so please contact sales team to verify before ordering.