
KosinTec®





Small Size Plastic Shell Wall Mount Display

Kosintec's Small size wall mount display with plastic housing, Lightweight body that is easy to install. Screen with capacitive touch optional, Multiple size optional, Display widely applicable for shopping malls, hotels, office buildings, restaurants, service halls, elevator lobbies and many other scenarios.

DW1013T

• Optimal Visual Clarity
- High-performance image processor.
- Delivers true color expression and high resolution.
- Offers adjustable picture quality and white balance.

• Anti-reflection Anti-glare Surface Optional
- Higher haze panel
- Anti-reflection and anti-glare effects.

• Fail Over Support

• GPlay Convenient U disk
- Simply insert the U disk for automatic content copying and playback on the device upon booting

• CMS / Remote Management Support (optional)
- Cloud-based remote management (CetusMSC) and CMS platform (GalaxyASC) support.
- Real-time monitoring of display status, parameters adjustment, and content distribution.
- Remote control via PC and Smart phone.

• Built-in Speaker

• Open API & SDK Support and RS232 Compatible

• Landscape/Portrait Compatible
- Portrait and landscape display orientations.

• OTA Firmware Update
- Enables remote firmware and application updates.
- Designed for seamless upgrades.

• Fire Protection Certification

• Extended Product Warranty
- Engineered for long-term durability.
- Guarantees reliable 24/7 operation.
- Comprehensive warranty ensures customer satisfaction and confidence.

Specification

Hardware Specification

Panel	IPS
Display Size	10.1 inch
Protection Glass	N/A
Protection Level	/
Front Color	Black/White
Set Dimension (L*W*D)	244.18×163.17×27.74mm
Bezel Width Width(mm)	10.99mm
Active Display Area(H*V)	218.5mm x137.5mm
Resolution	1280 x 800
Type	60Hz E-LED BLU
Brightness(Typ.)	250 cd/m²
Contrast Ratio(Typ.)	1500:1
Haze	25%
Viewing Angle(H/V)	178°(H) X 178°(V)(CR≥10)
Chromaticity	16.7M
Color Gamut	72%
Response Time	6ms (Typ)
Operation Hour	24/7
Panel Orientation	Landscape/Portrait
Connectivity	USB *2, DC in *1,RJ45*1
Power Input Supply	100-240V AC， 50/60Hz
Power Consumption	18W
Speaker	4Ω5W*2
IR	/
Touch Technology	PCAP Touch Optional
Camera	N/A
Installation	Wall mount
VESA Mount	75 x 75 mm
Package(W*H*D)	To be advise
Weight (kg)	To be advise
Operating Temperature	0°C~+50°C
Storage Temperature	-5°C~+60°C

System Specification

CPU	A40
GPU	/
Operating System	Android 7.1
Cloud Advertising Distribution System	Optional
Cloud Splice System	Optional
Memory	DDR 1G
Storage	EMMC 8GB
Ethernet	Ethernet (RJ45) WiFi 802.11b/g/n 4G LTE(FDD/TDD)(Optional)
Panel Image Rotation	0/90/180/270/360 Angle Rotation
Video Decoder	MPEG-1/2/4,H.264,HEVC,VP8,VP9,AVS+,AVS2.AV1
Audio Decoder	MPEG-1.MPEG-2(layerI/II),MP3,AAC-LC,HE-AAC
Picture Decoding	JPG,JPEG ,PNG ,BMP

What's in the box


Power Cable	x 1 Power cord (based on region)
Adaptorl	x 1
Wall Mount Bracket	x 1

Warranty

Warranty	1 year

Dimensions

Unit: mm



10.1-inch Screen
Six Views

* Compatibility may differ by equipment.
* Software compatibility may change over time. Please contact your regional sales representative for details.
* Specifications are subject to change without notice, so please contact sales team to verify before ordering.