



ATTESTATION of conformity with European Directives

BV LCIE CHINA Number 2366AS09ASAP51546

Product Hybrid Inverter

Reference SSE-HH3K-P1-EU, SSE-HH3K7-P1-EU, SSE-HH4K6-P1-EU, SSE-HH5K-P1-EU, SSE-HH6K-P1-EU, SSE-HH3K-P1-AU, SSE-HH3K7-P1-AU, SSE-HH4K6-P1-AU, SSE-HH5K-P1-AU, SSE-HH6K-P1-AU

Issued to Shenzhen Sosen Innovation Technology Co Ltd

Address 601, Pengzhanhui, Building 1, No.233, Xinqiao Community Center Road, Xinqiao Street, Bao'an District, Shenzhen, China

Manufacturer Suzhou Northern Electric Power Technology Co.,Ltd

Technical characteristics See below table

The submitted sample of the above equipment has been tested for **CE** marking according to following European Directive and following standards:

LVD Directive 2014/35/EU *

* Thanks to note that from April 20th 2016; this directive will be replaced by the new LVD directive, 2014/35/EU.

<i>Standards</i>	<i>Report number</i>	<i>Report date</i>
IEC 62109-1:2010 / EN 62109-1:2010	ASAP-ESH-P23030277-1	2023-09-18
IEC 62109-2:2011/ EN 62109-2:2011	ASAP-ESH-P23030277-2	

The referred test report(s) show that the product complies with standard(s) recognized as giving presumption of compliance with the essential requirements in the specified European Directive

This verification does not imply assessment of the production of the product

The **CE** marking may be affixed if all relevant and effective European Directives with **CE** are applicable

Shanghai (P.R. China), Sep 20rd, 2023



This document shall not be reproduced, except in full, without the written approval of BV LCIE China. Information given in this document are related to the tested specimen of the described electrical sample.

Version: 3.0 / Feb.10, 2021



**BUREAU
VERITAS**

Model / Type for EU	SSE-HH3K- P1-EU	SSE-HH3K7- P1-EU	SSE-HH4K6- P1-EU	SSE-HH5K- P1-EU	SSE-HH6K- P1-EU
Model / Type for AU	SSE-HH3K- P1-AU	SSE-HH3K7- P1-AU	SSE-HH4K6- P1-AU	SSE-HH5K- P1-AU	SSE-HH6K- P1-AU
MPP DC voltage range [V].....	80-550				
Max. Input DC voltage [V].....	600				
Max. Input DC current [A]	16A*2				
Output AC voltage [V].....	230				
Max. Output AC current [A].....	13	16	20	21,7	26,1
Rated output power [VA]	3000	3680	4600	5000	6000