

Product Model(Su

Pic.



Product Ap

Type	Spec.	
Product	Product Type	
	Dimension	
	Case Material	
	Weight	

System Hardware

Type	Spec.	
CPU	Model	Int
	Speed	2.3GHz (8259
	Max. Turbo Speed	3.8GHz 8259I
	Power Consumption	28W
Memory	Model	
	Capacity	1x9
Storage	EMMC	
	SSD	M.2
	2.5" SSD	2.5
	TF Slot	Star
RTC	BIOS	F
Auto Power On	BIOS	Suppo
diskless Netwo	BIOS	Suppor
TPM	CPU integratesTPM	
Dual Display	Video Output	Sup
LED	State	

Internet Co

Type	Spec.	
WIFI	Model	M
	Protocol	
Bluetooth	Model	I
	Protocol	
3G	Built-in	

4G	Built-in	
Ethernet	LAN1	10M
I/C		
Type	Spec.	
USB	USB2.0	
USB	USB3.0	
TF	Expansion Memory	
HDMI	AV Output	
VGA	Video Output	
RJ45	Gigabyte Ethernet	
Finger Print	Password	
type_c	Data Transmission	Type_c support
POWER	Power Button	
DC IN	Power Supply Input	
Audio-in	Audio-in	
Audio-out	Audio-out	
Antenna1	FPC Antenna	
Antenna2	FPC Antenna	
SIM	Micro SIM	
Software Cor		
Type	Spec.	
OS	Version	Win10 Hc
Environ		
Type	Spec.	
Environment	Working Temperature	
	Memory Temperature	
	Humidity	90%
Access		
Type	Spec.	
Power Supply	Vesa	Input 100~240V
Remote Cont		No Supp

VESA Mount



Subject): **CK10 A**



Appearance	
Description	Optional
MINI PC, Ad Terminal Box	
137.5mm*126mm*50mm	
Plastic	
Net Weight 561g	
Basic Configuration	
Description	Optional
Intel i5-8259U, 8279U, 10210U	
U); 2.4GHz (8279U); 1.6GHz(10210U)	
J); 4.1GHz (8279U); 4.2GHz(10210U)	
(8259U, 8279U) 15W (10210U)	
1xSO-DIMMDDR4	
SO-DIMMDDR4 Max 16GB	
No Supporting	
2280 M.2 NVMe/ NGFF, Max 2TB	
2.5" SATA, Max 2TB, Optional	
Standard TF Slot, Max. to 128GB	
Real-time Clock, Time Boot	
Support auto power on after electrified	
Support uefi/Legacy Diskless Switch On	
Support TPM 2.0	
Support DP+HDMI1 Dual Display	
Green light- Switch on	
Red light- Switch off	
Connection	
Description	Optional
M.2 E_key intel 7265/ 3165	
IEEE 802.11 a, b/g, n, ac	
M.2 E_key intel 7265/ 3165	
Support Bluetooth 4.2	
M.2 B_key 2242	Optional

M.2 B_Key 2242	Optional
1/100M/1000M Self-adaption	
Port	
Description	Optional
USB2.0 Type-A*2	
USB3.0 Type-A*4	
TF*1	
HDMI 1.4b Type A x1	
VGA x1	
RJ45 x1	
Support lock/unlock	
Port expansion, Data Transmission/AV I/O	
x1	
5.5/2.1mm DC Jack x1	
3.5mm Phone Jack x1	
3.5mm Phone Jack x1	
WiFi+BT x2	Optional
3G/4G x2	Optional
SIM x1	TF after opening cover
OS Configuration	
Description	Optional
Android/Win10 pro/Win10 IOT/ Ubuntu	
Environment	
Description	Optional
0~40°C	
-20~60°C	
85% @ 40 °C (No Condensation)	
Power Supply	
Description	Optional
50/60Hz Output19V/4.7A DC 5.5*2.1mm	
Mounting	



117mm*45m
m