

Model: IPC X1		
Processor	CPU	Celoron 2950U/2980U , Intel® Core 4100U/4200U/4300U /4500U/Processors
	BIOS	AMI Source Code
	Chipset	SOC
Memory	RAM	4GB/8GB
	ROM	32GB/64GB
	Type	DDR3 -1866/1600MHZ
Memory	Socket	1 x SO-DIMM
	Max Size	8GB
	GPU	Intel® UHD Graphics 440
Graphics	HDMI	1 x HDMI (Max. 3840 x 2160 @30Hz)
	VGA	1 x VGA (Max. 1920 x 1080 @30Hz)
	DP	1 x DP (Max. 4096 x 2304 @60Hz)
Network	Controller #1	Realtek 8111F Gigabit Ethernet
	Interface	2 x RJ45
I/O	USB	4 x USB 3.0, 2 x USB 2.0
	Display Interface	1 x HDMI, 1 x VGA 1xDP
	LAN	2 x RJ45
	Serial Port	1XRS232
	Audio	1 x MIC-IN, 1 x AUDIO-OUT
	mSATA	1 x Full-size mSATA
	JAHC Switch	1
	SIM	1 x SIM Slot
	LED Indicators	1 x Sleep LED, 1 x Power LED
Storage	SATA	1 x 2.5" SATA
	mSATA	1 x Full-size mSATA
	PCIE	1* Mini_pcie
JAHC Tech	WatchDog	Timer 0~255 Second Time Out Support
	Auto Power On	Power Activated Automatically Start
	RTC	Set Up Independently Every day, A Week as a Cycle
	Remote Control	/
	Wake On Lan	Supported
Operation System	Windows	Windows 10 (64 bit)
	Linux	Supported
Power	Power Type	DC-In
	Power Adapter	12V/4A
Mechanical	Dimensions (W x D x H)	137mm*121mm*38mm
	Fanless	Yes
	Construction	Met ^{al} Pl ^{astic}
	Mounting(Optional)	Desk/Wall Mounting and VESA Mounting Kit
	Color	Black
Environment	Environment	0°C ~ 40°C (32 °F ~ 104 °F) at 0.7m/s Air Flow
	Relative Humidity	95% @ 40°C (non-condensing)