

# Specifications

Model	LT800	LT810	LT800 Pro	LT810 Pro	LT880(HRS)*
Material	Precision coating	Stainless steel	Precision coating	Stainless steel	Precision coating
Printing Performance	1-4 Lines (7X5matrix) 1-5 Lines(5X5 matrix) Max. speed=206m/min@5X5		1-4 Lines (7X5matrix) 1-5 Lines(5X5 matrix) Max. speed=344m/min@5X5		1-4 Lines (7X5matrix) 1-5 Lines(5X5 matrix) Max. speed=430m/min@5X5
Font Matrix	Single-Line:5X5,7X5,9x6,12X8,16X11,19X14,24X17,32X22 3 Lines:5X5,7X5,9x6 5 Lines:5X5 Twin-Line:5X5,7X5,9x6,12X8,16X11 4 Lines:5X5,7X5				, , , , ,
Printing Distance	Font Height:1-15mm Printing distance:2mm to 30 mm Best:10mm				
Operating System	LT-Touch unique System, Multiple Languages				
Print Content	$English, Chinese, Arabic  Numbers,  Serial  number,  Barcode,  Shift,  DM/QR  Code,  UPC  A\&E,  EAN  8  \&  13,  GS1,  Logo,  UCC/EAN  128, \\ Code  128  A,  B  \&  C,  Code  39,  Code  125  , \\ Automatic  date/time/expiry  date,   Apecial  characters, etc.  Appendix  Append$				
Extra Memory	USB,RS485		USB,RS485,Ethernet		USB,RS485,Ethernet
System Language					
Memory Storage	1000+Messages		1000+Messages		1000+Messages
Industrial Protection	IP55		IP55		IP55
Printhead	Super soft, length 3m constant temperature,60µm		Super soft, length 3m constant temperature,60µm		Super soft, length 3m constant temperature,50µm
Printing Direction	360° All-round printing				
Cartridge Volume	Ink (500ml) Make-up (750ml)		Ink (500ml) Make-up (750ml)		Ink (500ml) Make-up (750ml)
Temperature/ Humidity range	0-45°C 0-95% Relative Humidity,Non-condensing				
Power	AC100-240V, 50/60Hz,80VA				

<sup>\*800/810</sup> is a standard model, 800Pro/810Pro is a high-speed version with Network function, and 880HRS is a high-speed, high-resolution, small font model (suitable for applications with high-precision fonts)

### **Dimensions**







### LEAD TECH (ZHU HAI) ELECTRONIC CO., LTD.

Tel:+86 756-7255629 Fax:+86 756-7255638 www.leadtech.ltd

Floor 3/4, Building 1, No. 728, Jinhu Road, Sanzao Town, Jinwan District,

Zhuhai City





SIMPLE | FRIENDLY | SMART | RELIABLE

LT800 Series Small character inkjet printer















Automatic

Cleaning





RS-485 Ethernet Data Data Interface Interface
















Viscosity Modular Adjust



### 1/Simple



#### Linux System, Simple Operation

7-inch Touch Screen, WYSIWYG

User friendly interface, allows quick operation Easy for messages editing







#### **New Generation Printhead**

Integrated Printhead Design

Easily aligned by a small tool, no need to disassemble, more reliable









#### Modular Design InkCore

Integrated Ink System

Modularized Components, Less Spare Parts More Stable & Reliable, Easy to Maintain








\*All major components are modularized, making it less spare parts! Printer is more stable and reliable, easy to maintain.

### 3/Smart



#### Multi-language System Support Remote Control

Real-time Monitoring printer status Up to 14 languages system menu and keyboard

Support editing your own font by

New Generation Logo Editor, for easy logo drawing







## 2/Friendly



#### **New Message Editor**

Support message data drag manually,

Precise adjustment by XY axis Support message data drag into DM/QR Code Support to edit longer message and logos join together More suitable for pipe industry application







#### **USB Hot Swap Function**

USB external expansion, simple and flexible

Support Txt. file database save to USB More Print Mode Selections Support record saving when power off



#### Support External Data Input

Remote Upgrade Software and Firmware

RS485, USB Ethernet









### 4/Reliable



#### **Teflon Coating Cabinet**

Nice Looking & Easy Cleaning

Stainless steel cabinet, stronger anti-interference



#### **New Innovative Printhead**

Sapphire Nozzle, Constant Temp Printhead Design

Reduce Nozzle Blockage, Less Cleaning Time Integrated Printhead Design, Prevent Ink Leaking Modified Font Drawing, More Beautiful 30mm Print Distance, Perfect & Clear Print Support Large & Small Font Setting







EXE PRINTING SAMPLE 0123456789 9X7 PRINTING SAMPLE 0123456789

12X9 PRINTING SAMPLE 813345

16X11 PRINTING SAMPLE 19X14 PRINTING SAMPLE



