

Description	Atlas D160-CE-SE
Input Voltage	400 V AC $\pm$ 10%
Input Current	231 A (per phase)
Power	160 kW
Frequency	50/60 Hz $\pm$ 10%
AC wiring	3P+N+PE
Output Voltage	200V DC-1000V DC
Output Current	200 A
Three outlets	2* CCS2 + Type 2 (22KW) socket
HDMI	15" High brightness full color touch screen display
Network	Ethernet, Wi-Fi, SIM card (2G / 3G / 4G)
Protocol	OCPP 1.6J, support upgrade to OCPP 2.0.1
Electrical Protection	Protection against short circuit, over-voltage, under-voltage, over temperature,surge, lightning; Detection of grounding, insulation, phase deficiency; RCD: AC outlet-Type A+6 mA; DC outlet-Type A
Hardware	Emergency stop button
Rating	IP54, IK10 (screen IK08)
Standards	IEC 61851-1, IEC 61851-23, IEC 61851-21-2, RoHS
Online	1. APP 2. RFID: ISO 14443 mifare1 3. POS (visa/master card, debit card, Apple pay, Google pay) 4. ISO 15118
Offline	1. White-listed RFID card 2. Password
Dimensions	(H x W x D) 1880 x 850 x 600 mm
Weight	<450 KG
Cable	Standard: 5 m;
Storage Temp.	-40°C to +80°C

Atlas DC Charging Solution

Future Proof Investment

- 2 * CCS 2 + Type 2 (22KW)socket

Easy Maintenance

- Unique module pre-installation design
- Automatic inspection platform
- Remote diagnostics and OTA upgrade

Exceptional User Experience

- Low noise design, $\leq$ 60 dB (A)
- Support APP, NFC, credit card, Plug & Charge

Safe and Reliable

- 53-fold electrical protections
- Galvanized metal cabinet
- Smart charging

MARUIKEL



Description	Atlas D160-CE-SE
Standby power	<80W
Installation	Ground
Storage Temp.	-40°C to +80°C
Operation Temp.	-30°C to +55°C
Humidity	5% to 95%
Altitude	$\leq$ 2000 m
Noise	$\leq$ 60 dB(A)
Material	Galvanized metal
Warranty	3 years