



FUNCTIONS 功能

- Dual DC output interface: Equipped with two DC output interfaces, it can power two devices at the same time to meet the power needs of multiple devices.
 双DC输出接口: 配备两个DC输出接口, 可同时为两台设备供电, 满足多设备用电需求。
- Fast switching: The built-in circuit provides parallel power supply. When the mains is disconnected, the 0ms conversion time provides continuous power supply.
 快速切换: 内置电路提供并联供电方式, 当市电断开时, 0ms转换时间以提供持续的供电。
- Multiple protections: It has multiple protection functions such as overcharge, over-discharge, overcurrent, short circuit, etc., which effectively prolongs the battery life and ensures the safety of the device.
 多重保护: 具备过充、过放、过流、短路等多重保护功能, 有效延长电池寿命, 保障设备安全。
- Installation method: Small size, light weight, wall-mounted installation, easy to operate.
 安装方式: 体积小, 重量轻, 壁挂式安装, 操作简单。
- LED indicator: It is equipped with an LED indicator to display the working status and power status in real time, so that users can understand the operating status of the device.
 LED指示灯: 配备LED指示灯, 实时显示工作状态和电量情况, 方便用户了解设备运行状态。

Notes:

- * CV: Constant Voltage * WRV: Wide Range Voltage
- * DC port: Generally use 55*21mm or 55*25mm DC port
- * Solutions to adapt to different powered devices can be provided according to customers
- * Support customized voltage/current/capacity/outer packaging/LOGO, etc.

OL4 Dual DC Mini UPS Series

TECHNICAL SPECIFICATION 技术规格

Model 型号	OL4W-20632	OL4W-26632	OL4W-32632	OL4W-35632	OL4W-20661	OL4W-26631	OL4W-32661	OL4W-35661
Input 输入	12.6V2A 55*21DC				25.2V1A 55*21 DC			
Output 输出	USB 5V2A							
	8.25V ~ 12.6V/3A Wide-Range Voltage (WRV) DC				16.5V ~ 25.2V/3A Wide-Range Voltage (WRV) DC			
Output power(Max) 输出最大功率	36W				60W			
Battery type 电池型号	18650 Lithium-ion							
Nominal voltage 标称电压	11.1V				22.2V			
Battery qty & capacity 电池数量与容量	6×2000mAh	6×2600mAh	6×3200mAh	6×3500mAh	6×2000mAh	6×2600mAh	6×3200mAh	6×3500mAh
Rated capacity 额定容量	44.4Wh	57.72Wh	71.04Wh	77.7Wh	44.4Wh	57.72Wh	71.04Wh	77.7Wh
Protection 保护	Over-charge, Over-discharge, Over-current, Overload, Over-temperature and short circuit							
LED indicator light LED指示灯	1 LED lights up at 0%~20% 2 LEDs light up at 21%~40% 3 LEDs light up at 41%~60% 4 LEDs light up at 61%~80% 5 LEDs light up at 81%~100%							
Operating temperature 工作温度	-10℃~50℃							
Storage temperature 储存温度	-20℃~65℃							
Relative humidity 相对湿度	10%- 90% RH							
Installation method 安装方式	Wall-mounted							
Dimension 尺寸	5.83×3.33×1.10 inch / 148.0×84.5×28mm							
N.W. 净重	approx 395g							
Accessory 配件	1pcs 12.6V2A DC Charger 1pcs DC Y-Cable: 1 Female to 2 Male				1pcs 25.2V1A DC Charger 1pcs DC Y-Cable: 1 Female to 2 Male			