



FUNCTIONS 功能

- **USB interface:** The device is powered through the USB interface, suitable for USB devices such as mobile phones and tablets.
USB接口:通过USB接口为设备供电,适用于手机、平板、等USB设备。
- **Fast switching:** The built-in circuit provides parallel power supply. When the mains is disconnected, the 0ms conversion time provides continuous power supply.
快速切换:内置电路提供并联供电方式,当市电断开时,0ms转换时间以提供持续的供电。
- **Multiple protections:** It has multiple protection functions such as overcharge, over-discharge, overcurrent, short circuit, etc., which effectively prolongs the battery life and ensures the safety of the device.
多重保护:具备过充、过放、过流、短路等多重保护功能,有效延长电池寿命,保障设备安全。
- **Compact and portable:** It is small in size, light in weight, easy to carry and install, and suitable for various occasions.
小巧便携:体积小,重量轻,便于携带和安装,适用于各种场合。
- **LED indicator:** It is equipped with an LED indicator to display the working status and power status in real time, so that users can understand the operating status of the device.
LED指示灯:配备LED指示灯,实时显示工作状态和电量情况,方便用户了解设备运行状态。

Notes:

- * CV: Constant Voltage * WRV: Wide Range Voltage
- * DC port: Generally use 55*21mm or 55*25mm DC port
- * Solutions to adapt to different powered devices can be provided according to customers
- * Support customized voltage/current/capacity/outer packaging/LOGO, etc.

OL4 USB DC Mini UPS Series

TECHNICAL SPECIFICATION 技术规格

Model 型号	OL4-USB20632	OL4-USB26632	OL4-USB32632	OL4-USB35632	OL4-USB20661	OL4-USB26661	OL4-USB32661	OL4-USB35661
Input 输入	12.6V2A 55*21DC				25.2V1A 55*21 DC			
Output 输出	USB 5V2A							
	8.25V ~ 12.6V/3A Wide-Range Voltage (WRV) 55*21DC				16.5V ~ 25.2V/3A Wide-Range Voltage (WRV) 55*21DC			
Output power(Max) 输出最大功率	36W				60W			
Battery type 电池型号	18650 Lithium-ion							
Nominal voltage 标称电压	11.1V				22.2V			
Battery qty & capacity 电池数量与容量	6×2000mAh	6×2600mAh	6×3200mAh	6×3500mAh	6×2000mAh	6×2600mAh	6×3200mAh	6×3500mAh
Rated capacity 额定容量	44.4Wh	57.72Wh	71.04Wh	77.7Wh	44.4Wh	57.72Wh	71.04Wh	77.7Wh
Protection 保护	Over-charge, Over-discharge, Over-current, Overload, Over-temperature and short circuit							
LED indicator light LED指示灯	1 LED lights up at 0%~20% 2 LEDs light up at 21%~40% 3 LEDs light up at 41%~60% 4 LEDs light up at 61%~80% 5 LEDs light up at 81%~100%							
Operating temperature 工作温度	-10℃~50℃							
Storage temperature 储存温度	-20℃~65℃							
Relative humidity 相对湿度	10%- 90% RH							
Dimension 尺寸	5.83×3.33×1.10 inch / 148.0*84.5*28mm							
N.W. 净重	approx 390g							
Accessory 配件	1pcs 12.6V2A DC Charger 1pcs DC Y-Cable: 1 Male to 2 Female				1pcs 25.2V1A DC Charger 1pcs DC Y-Cable: 1 Male to 2 Female			