Tel: +86-10-62198496 Fax: +86 010 62985217 www.dorland-tech.com tian@dorland.com.cn



DORLAND Industrial Intrinsically Safe Smartphone Unicorn10 PRO

DORLAND System Control Technology Co., Ltd. recently introduced the intrinsically safe smartphone Unicorn10 PRO. It adopts advanced technology, intrinsically safe circuit design, domineering appearance and solid body. The mobile phone adopts 6.56 inch full screen (20:9) design, equipped with 8MP front and 50MP + 0.3MP pixel high-definition camera at the rear. Its waterproof and dustproof performance meets the international IP68 standard.

In addition, the phone supports NFC, fingerprint unlocking and other functions. This is equipped with GPS positioning, compass and other functions suitable for outdoor construction and pipeline inspection. It can cooperate with OA office system, patrol positioning system, data acquisition system and other applications. Especially suitable for hazardous explosion environment, such as petroleum, chemical, pharmaceutical, oil depot, tank farm and other dangerous places with combustible and explosive gas, which is convenient for users to communicate with production and scheduling in time.

Protection Grade: IP68

Marking: Ex ib IIC T4 Gb / Ex ibD 21 T130°C

Certificate No.: CCRI 20.2303

OS: Android 14.0

Screen: 6.56inches (20:9) 720*1612 HD+

Secondary screen: 1.54" IPS TFT

Memory: 8GB+256GB (RAM expansion 4GB/8GB/12GB with three levels of over clocking)

Storage Card: support T-flash card, Up to 2TB

CPU: 8cores T606 2 x A75@1.6GHz + 6xA55 1.6GHz

Cameras: Rear camera 50MP + 0.3MP

Front camera 8MP

Battery: 8000mAh

Battery voltage: 3.8V

Frequency: GSM:B2/3/5/8

WCDMA: B1/2/4/5/8 TDD:B34/38/39/40/41

FDD:1/2/3/4/5/7/8/18/19/20/25/26/28AB/66

EDGE/GPRS: Yes

GPS: Beidou, Galileo, Glonass, GPS

Bluetooth: BT5.0

DORLAND

www.dorland-tech.com













www.dorland-tech.com tian@dorland.com.cn

DORLAND www.dorland-tech.com









		1	
	Certificate	Description	
Certificate	Marking	Ex ib IIC T4 Gb / Ex ibD 21 T130°C	
	Certificate No.	CCRI 20.2303	
	Protection Grade	IP68	
Items		Description	
Product	Dimension (mm)	174*81.2*15.8mm	
overview	Weight (g)	326g	
Hardware configuration		Description	
	OS	Android 14.0	
	Feature	8cores T606	
CPU		2 x A75@1.6GHz + 6xA55 1.6GHz	
	Framework	Mali G57 1core	
	Technology	12nm	
GPU	GPU model	Mali-G57 GPU	
	Vidoo oncodo	FHD 60fps	
Video	Video encode	H.263/264/265/VP8/VP9	
video	Video decode	FHD 60fps	
		H.263/264/265/VP8/VP9	
	Network	GSM/WCDMA/FDD/TDD	
network		GSM:B2/3/5/8	
	Frequency	WCDMA: B1/2/4/5/8	
network		TDD:B34/38/39/40/41	
		FDD:1/2/3/4/5/7/8/18/19/20/25/26/28AB/66	
	EDGE/GPRS	Support	
	memory	8GB+256GB (RAM expansion 4GB/8GB/12GB)	
		with three levels of over clocking) LPDDR4X +	
Storage		UFS	
Storage	SIM card type	SUPPORT Nano SIM+Nano SIM+TF card	
	Memory card type	T-flash card	
	Expanded memory	Up to 2TB	
		Camera 8MP	
	Sensor	Hynix Hi-842	
	Sensing area	1/4 inch 4P	
Front Camera	Pixel area	3264*2448 8MP	
Front Camera	Aperture	F/2.2±5%	
	Field of view angle	78°	
	Focus mode	FF	
Rear Camera 50MP+0.3MP(Without function)			
Rear Camera	Sensor	Omnivision OV50C40	
	Sensing area	1/2.5 inch 5P	

DORLAND www.dorland-tech.com

	T	www.dorland-tech.com
	Pixel area	8192*6144
	Aperture	F/1.8±5%
	Optical zoom	N/A
	Field of view angle	77°
	Focus mode	AF
	Flash led	Support
	Size & technology	6.56 inch IPS Blind hole screen 90Hz
	Screen color	16.7M
	Туре	in-cell
	resolving power	720*1612 HD+
Display	Pixel density	269
	Screen aspect ratio	20:9
	Screen-to-body ratio	84%
	Brightness	380 cd/m2(Typ)
	Screen contrast	1500:1
	Size & technology	1.54 IPS TFT
	Screen color	262K
	Туре	LCD
	Resolution	240*240
Secondary	Pixel density	220 PPI
screen	Aspect Ratio	1:01
	Brightness	400 cd/m2(Typ) LCM
	Screen contrast	1000:1
	Display	Display information such as temperature,
		humidity, time, date, week, air quality, etc
	navigation	Support (Beidou,Galileo,Glonass,GPS)
	WIFI	Support 2.4G/5G (802.11ac/a/b/g/n)
Transmission	Bluetooth	Support BT5.0
function	FM	Support
	OTG	Support
	NFC	Support
Sensor	G-sensor	Support
	Proximity sensor	Support
	Ambient light senor	Support
	Compass (magnetic)	Support
	Geomagnetism	Support, support reverse charging
Unlock method fingerprint	fingerprint location	Side fingerprint
Physical buttons	Power button	Support
	Volume button	Support
	Custom key function	Support, After selecting the corresponding custom
•	•	

Tel: +86-10-62198496 Fax: +86 010 62985217 www.dorland-tech.com tian@dorland.com.cn

DORLAND www.dorland-tech.com

		www.dorland-tech.com
		function in the settings, click and long press to
		achieve the function
Virtual buttons	Home button home	Support
	Menu button	Support
	Return button	Support
Port	Headphone port	TYPE-C to 3.5mm headphone jack interface
	Charger interface	Type-c
Battery	Capacity	8000mAh
	Safe charging and	500 times
	discharging frequency	500 times
	Material	Lithium cobalt oxide
	Voltage	3.87V
	discharge coefficient	MAX 0.5C
	Battery density ratio	685Wh/L
Software function		Description
System function	System navigation	Gesture navigation, "three-button" navigation
	Smart gesture	Three finger screenshot, intelligent motion sensing
	FOTA upgrade OTA	Support
	Supported languages	English, Spanish, Simplified Chinese, Traditional Chinese. (It has updated 48 languages)
Entertainment	Video playback	Support MP4、AVI、MKV、MOV、FLV、M4V and other video formats, up to 1080P / 30fps
	Video produce	Highest Support 1080P@30fps video shooting
	Audioplayer	Support MP3, M4A, AAC, MKA, AMRAnd other video formats
	Graphic format	Support JPEG, BMP, GIF,PNG etc.
	Game	Support

www.dorland-tech.com tian@dorland.com.cn



www.dorland-tech.com





CONFORMITY CERTIFICATE OF EXPLOSION-PROOF

Certificate No.:

CCRI 20.2303

Company: Beijing Dorland System Control Tech Co.,Ltd

Address: Room 807, Yingu Plaza, North 4th Ring West Road, Haidian District, Beijing 100080, P.R. China

Name of Product: **Industrial Intrinsically Safe Smartphone**

Unicorn10 Type of Product:

Ex ib II C T4 Gb / Ex ibD 21 T130°C Marking:

Technical Documents: O/DLM 006-2020

Unicorn10-00 Drawing No.:

1. Power supply by dual protection rechargeable lithiumion Note(s): battery with rated voltage 3.8VDC,

nominal napacity:8000mAh;

2.Ambient temperature range:-20°C≤Ta≤+60°C;

3. IP code: IP68 @1.5m,30min.

By verifying the drawings and technical documents and checking samples, the product complies with the following standards currently valid in P.R.China:

> GB 3836.1-2010, GB 3836.4-2010, GB/T 4208-2017 GB 12476.1-2013, GB 12476.4-2010

Date of Issue: 8.3.2020

Valid till: 8.2.2025

Authorize:

Test Center Of China Coal Research Institute (煤炭科学技术研究院有限公司检测中心)

(The test center of the national safety production of mining equipment and mining oil in Beijing) Note: This certificate is only valid for the products that are in accord with samples tested and verified. Center Add: No.5 Qingniangou Road, Hepingli, Beijing, 100013 Tel/fax: 010-89268018 The query url of Explosion-proof Certificate: http://www.ccritc.com.cn/Home