



PATIENT MONITOR

2022 Catalog



SHANGHAI RO-CHAIN MEDICAL CO.,LTD

Address: Room 207, Building 1, Kangqiao Road 787, Pudong New District, Shanghai, China

Tel: 0086-21-58055329 Fax: 0086-21-58055330

Mobile(WhatsApp):0086-13248293519

E-mail: SevenY@ro-chainmed.com

Official website: www.ro-chainmed.com



SHANGHAI RO-CHAIN MEDICAL CO.,LTD

PRODUCT index

1.

VITAL SIGN PATIENT MONITOR



2.

PARAMETER PATIENT MONITOR



3.

MODULAR PATIENT MONITOR



4.

SEMI-MODULAR PATIENT MONITOR



5.

FETAL MONITOR





Vital sign Patient Monitor

Model No: RC-PM8000A

Application

Adult/Pediatric/Neonatal/Medicine/Surgery/ Operating Room/ICU/CCU

Features

- 5 Standard parameters: ECG, NIBP, SpO2, RESP, PR/HR.
- 7 inch high resolution color TFT LCD display.
- Real time S-T segment analysis, pace-maker detection.
- Indication of Incorrect manipulation and malfunction analysis.
- Patient info input management function.
- Multi-lead ECG waveforms display in phase.
- Large volume of tabular and graphic trends information storage and easy to recall.
- Capture dynamic waveforms.
- Efficient resistance to interference of defibrillator and HF knife.
- UP to 5 hours working capacity of built-in rechargeable lithium battery.

Standard Package

- | | | |
|------------------------------------|-----------------------|-------------|
| ■ RC-PM8000A main unit (7" screen) | ■ NIBP cuff & tube | ■ ECG cable |
| ■ SpO2 sensor | ■ Lithium-ion battery | |

System Inputs & Outputs

NIBP/SpO2/Temp/ECG/IBP Sensor Sockets RJ45 port

Optional Accessories

Touch screen, Trolley bracket, Hanging bracket, Monitor recorder, Vehicle-mounted power supply

Multi-parameter Patient Monitor

Model No: RC-PM8000c



Application

Adult/Pediatric/Neonatal/Medicine/Surgery/ Operating Room/ICU/CCU

Features

- 12.1" and 15" high resolution color TFT LCD display.
- 6 Standard parameters: ECG, RESP, NIBP, SPO2, 2-TEMP, PR/HR.
- Real time S-T segment analysis, pace-maker detection.
- Indication of Incorrect manipulation and malfunction analysis.
- Patient info input management function.
- Multi-lead ECG waveforms display in phase.
- Large volume of tabular and graphic trends information storage and easy to recall.
- Capture dynamic waveforms.
- Efficient resistance to interference of defibrillator and HF knife.
- UP to 2 hours working capacity of built-in rechargeable battery.
- Unique accessory management cabinet.
- Networking capacity.
- Option: IBP, ETCO2 and 2-IBP.

Standard Package

- | | | |
|------------------------|---------------------|-----------------------|
| ■ RC-PM8000C main unit | ■ 12.1"screen) NIBP | ■ ECG cable |
| ■ SpO2 sensor | ■ Temperature probe | ■ Lithium-ion battery |
| ■ NIBP cuff & tube | | |

System Inputs & Outputs

NIBP/SpO2/Temp/ECG/IBP Sensor Sockets RJ45 port

Optional Accessories

Touch screen, Trolley bracket, Hanging bracket, Monitor recorder, Vehicle-mounted power supply

Multi-parameter Patient Monitor

Model No: RC-PM8000D

Application

Adult/Pediatric/Neonatal/Medicine/Surgery/ Operating Room/ICU/CCU

Features

- 15" high resolution color TFT LCD display.
- 6 Standard parameters: ECG, RESP, NIBP, SPO2, 2-TEMP, PR/HR.
- Real time S-T segment analysis, pace-maker detection.
- Indication of Incorrect manipulation and malfunction analysis.
- Patient info input management function.
- Multi-lead ECG waveforms display in phase.
- Large volume of tabular and graphic trends information storage and easy to recall.
- Capture dynamic waveforms.
- Efficient resistance to interference of defibrillator and HF knife.
- UP to 2 hours working capacity of built-in rechargeable battery.
- Unique accessory management cabinet.
- Networking capacity.
- Option: IBP, ETCO2 and 2-IBP.

Standard Package

- | | | |
|------------------------|--------------------|-----------------------|
| ■ RC-PM8000D main unit | ■ (15"screen) NIBP | ■ NIBP cuff & tube |
| ■ ECG cable | ■ SpO2 sensor | ■ Lithium-ion battery |
| ■ Temperature probe | | |

System Inputs & Outputs

NIBP/SpO2/Temp/ECG/IBP Sensor Sockets RJ45 port

Optional Accessories

Touch screen, Trolley bracket, Hanging bracket, Monitor recorder, Vehicle-mounted power supply



Parameter Patient monitor


Model No: RC-STAR8000E

Standard Configuration

3 -lead ECG, RESP, Comen SpO₂, NIBP, HR,
Temp(Single Channel)

Optional Configuration

Dual-IBP, EtCO₂, Dual-Temp, Nellcor/Masimo SpO₂,
5/12-lead ECG, Thermal Recorder, Suntech NIBP,
Trolley, Wall mount, Ground wire



Parameter Patient monitor

Model No: STAR8000F

Standard Configuration

3-lead ECG, RESP, Comen SpO2, NIBP, HR, Temp (Single Channel), Touch screen

Optional Configuration

Dual-IBP, EtCO2, Dual-Temp, Nellcor/Masimo SpO2, 5/12-lead ECG, Thermal Recorder, Suntech NIBP, Trolley, Wall mount, Ground wire



Parameter Patient monitor


Model No: RC-C86

Standard Configuration

5-lead ECG, RESP, Temp (Single Channel), COMEN SpO₂, NIBP, HR

Optional Configuration

Dual-IBP, EtCO₂, AG, ICG, C.O., BIS, Nellcor/Masimo SpO₂, 3/12-lead ECG, Thermal Recorder, Dual-Temp, Suntech NIBP, Trolley, Wall mount, Ground wire



Parameter Patient monitor


Model No: RC-C80

Standard Configuration

5-lead ECG, RESP, Temp (Single Channel), COMEN SpO2, NIBP, HR

Optional Configuration

Dual-IBP, EtCO2, AG, ICG, C.O., BIS, Nellcor/Masimo SpO2, 3/12-lead ECG, Thermal Recorder, Dual-Temp, Suntech NIBP, Trolley, Wall mount, Ground wire



support wire & wireless central monitoring system



Modular Patient monitor

Model No: RC-C70

Standard Configuration

5-lead ECG, RESP, Dual-Temp, Comen SpO2, NIBP, EtCO2 (Without sensor)

Optional Configuration

Masimo/Nellcor SpO2, Dual-IBP, AG, C.O., BIS, 3/12-lead ECG, Suntech NIBP, EtCO2, Thermal Recorder, ICG, Trolley, Wall mount, Ground wire NIBP, Trolley, Wall mount, Ground wire





Modular Patient monitor

Model No: RC-C90

Standard Configuration

5-lead ECG, RESP, Dual-Temp, COMEN SpO₂,
NIBP, EtCO₂ (Without sensor)

Optional Configuration

Masimo/Nellcor SpO₂, Dual-IBP, AG, C.O., BIS,
3/12-lead ECG, Suntech NIBP, EtCO₂, Thermal Recorder,
ICG, Trolley, Wall mount, Ground wire



Semi-modular patient monitor

Model No: RC-NC 12

Standard Configuration

3/5-lead ECG, RESP, Comen SpO2, Comen NIBP, Dual-Temp

Optional Configuration

Masimo/Nellcor SpO2, Suntech NIBP, Dual-IBP, Masimo AG, Comen C.O., Module BIS+AG, Masimo EtCO2, Respirationics EtCO2, 12-lead ECG, Trolley, Multi-functional connector (Nurse call, synchronized defibrillation), Thermal Recorder, Wall mount, Ground wire



RO-CHAIN

Fetal Monitor



Model No: RC-STAR5000E

Standard Configuration

FHR1, TOCO, FM, Recorder

Optional Configuration

Fetal Stimulator, FHR2, Trolley

Physical Characteristics

| | |
|-------------|-------------------|
| Size: | 287mm*232mm*90mm |
| Weight: | 5kg |
| Screen: | 5.7" color screen |
| Resolution: | 800*600 |
| Trace: | 6 Waveforms (Max) |



Fetal Monitor



Model No: RC-C21

Standard Configuration
FHR1, TOCO, FM, Recorder

Optional Configuration
Fetal Stimulator, FHR2, Trolley

Physical Characteristics

| | |
|--------------------------|------------------------------------|
| Product Size: | 340mm*270mm*95mm |
| Net Weight: | 5.5kg |
| Battery Type: | Rechargeable & Lithium-ion battery |
| Battery Capacity: | 4400mAh |
| Battery Recharging Time: | Maximum 5.5 hours for charging |
| Battery backup: | 4 hours for continuous working |
| Display: | 12.1" color TFT touch screen |
| Resolution: | 800*600 |
| Trace: | 6 Waveforms (Max) |

ACCESSORY Showcasing



Oxygen probe



Five conductance connecting wire



Blood pressure cuff



Blood pressure cuff extension tube



Temperature probe



Ground wire



Power cord



Lithium battery



User manual