## SHANDONG HIGHLAND HYDRAULIC SEIKO CO., LTD.

## **Hydraulic Test Table Function Choosing List**

According to your requirements, please select the function by making 'YES 'or "NO "

Select Main Technical Data and Function Required		Pressure		Flow Rate			Power						
		35mp	42mp	380L/min	450L/min	500L/min	90kw	110kw	132kw	160kw	200kw	250kw	315kw
Your Company is Hydraulic		Repair Factory					Manufacturer Manufacturer						
		Max displacement					Please list models you want to test						
Test Component	Opened-type hydraulic pump												
	Closed-type hydreaulic pump												
	High speed hydraulic motor												
	Low speed hydraulic motor												
				Max flo	ow .								
	Hydraulic valves set												
	Hydraulic cylinder												
Drive Mode	Electromotor												
	Diesel engine drive												
	Hydraulic motor												
	Power recovery												
Speed Range	1000r/min												
	0-1500r/min												
	0-2500r/min												
	0-3500r/min		_					_	_	_		_	_

Display Mode	Locale(Withour Computer)						
	Computer (long-distance)						
Working medium	Hydraulic oil						
Oil tank cubage	1300L						
	2000L						
Oil filtrate							
	No						
	Water cooler						
	Wind cooler						
Do you need torsional moment power test?  (yes or no)							
	Connect shaft 2 piece Outline drawing of connect shaft	1 sheet					
Voltage/Phases / Hertz	380V/3Phases/50Hz or others						
Other Requirements							