

Feature:





1. The light source directly adopts the light board, and the T8/T5 tube is not needed, and the

luminous efficiency is higher;

2. High-quality shell is durable, protection upgrade, trust guarantee, and flame retardant technology can be used safely;
3. The lamp body and the translucent cover are made of fireproof PC material, which has good flame retardancy; the protection grade is up to P65;
4. The lamp body and the transparent cover can be packaged separately, which effectively reduces the packaging volume and saves freight;
5. Available with transparent cover and opal cover; transparent cover, light transmittance 93%; milky white cover, light transmittance 83%;
6. The lamp body has two types: wide side and narrow side. The wide side light is soft and the glare is small; the narrow side cost is relatively low;
7. PC material has good wear resistance, folding resistance and pressure resistance; it can bend at 180 degrees without crack; the buckle has PC and stainless steel materials;
8. Using high-quality SMD2835 chip, high-quality constant current drive, stable and reliable performance, high luminous efficiency, long life and low maintenance cost;

Installation diagram





3



Applicable:

Widely used in factories, warehouses, walkways, schools, restaurants, underground parking lots and other places.





Parameter:

| Model number | SF04-600-20W | SF04-600-30W | SF04-1200-40W | SF04-1200-50W | SF04-1500-50W | SF04-1500-60W |
|-----------------------|--|-------------------|---------------------|-------------------|---------------------|-------------------|
| power | 20W | 30W | 40W | 50W | 50W | 60W |
| Lamp bead model | SMD2835 | SMD2835 | SMD2835 | SMD2835 | SMD2835 | SMD2835 |
| Number of lamp beads | 120 PCS | 120 PCS | 240 PCS | 240 PCS | 360 PCS | 360 PCS |
| Serial and parallel | 10P12S | 10P12S | 20P12S | 20P12S | 30P12S | 30P12S |
| Drive brand | BOKE/LFD | BOKE/LFD | BOKE/LFD | BOKE/LFD | BOKE/LFD | BOKE/LFD |
| Input voltage | 200~240VAC | 200~240VAC | 200~240VAC | 200~240VAC | 200~240VAC | 200~240VAC |
| The output voltage | 36V | 36V | 36V | 36V | 36V | 36V |
| Drive function | Conventional non-dimming, 1-10V/DALI dimming, optional; | | | | | |
| Protection level | IP65 | IP65 | IP65 | IP65 | IP65 | IP65 |
| Color temperature CCT | 3000~6500K | 3000~6500K | 3000~6500K | 3000~6500K | 3000~6500K | 3000~6500K |
| Color rendering CRI | >80 | >80 | >80 | >80 | >80 | >80 |
| Light effect | >130LM/W | >130LM/W | >130LM/W | >130LM/W | >130LM/W | >130LM/W |
| Beam angle | 120° | 120° | 120° | 120° | 120° | 120° |
| Ambient temperature | -30~50℃ | -30~50℃ | -30~50℃ | -30~50℃ | -30~50℃ | -30~50℃ |
| Lamp body material | PC lamp body + PC cover | | | | | |
| Lampshade material | High light transmission PC cover, milky white glossy/creamy stripes/transparent stripes (optional) | | | | | |
| Buckle material | PC/stainless steel, optional | | | | | |
| Number of buckles | 6个 | 6个 | 10个 | 10个 | 12个 | 12个 |
| Lamp body size | 600x95x80mm | 600x95x80mm | 1200x95x80mm | 1200x95x80mm | 1500x95x80mm | 1500x95x80mm |
| Life/Warranty period | 50000hrs / 5years | 50000hrs / 3years | 50000hrs / 3years | 50000hrs / 3years | 50000hrs / 3years | 50000hrs / 3years |
| certified product | TUV/CB/ROHS/ISO9001 | | TUV/CB/ROHS/ISO9001 | | TUV/CB/ROHS/ISO9001 | |



Product size drawing (unit: mm):



Packing data:

| Model | Product size/mm | Small Package /cm | Package dimensions /cm | QTY | Single N.W (KG) | FCL G.W (KG) |
|------------------|-----------------|-------------------|------------------------|-----|-----------------|--------------|
| SF04-600-N2-20T | 600x95x80 | 66x10x9 | 68x32x29 | 9 | 1.2 | 11.5 |
| SF04-1200-N2-40T | 1200x95x80 | 126x10x9 | 128x32x29 | 9 | 2.0 | 19.5 |
| SF04-1500-N2-50T | 1500x95x80 | 156x10x9 | 158x32x29 | 9 | 2.2 | 21.0 |
| SF04-1500-N2-60T | 1500x95x80 | 156x10x9 | 158x32x29 | 9 | 2.2 | 21.0 |
| SF04-600-W2-20T | 600x125x88 | 66x13x9.5 | 68x28x31 | 6 | 1.3 | 8.5 |
| SF04-1200-W2-40T | 1200x125x88 | 126x13x9.5 | 128x28x31 | 6 | 2.2 | 14.6 |
| SF04-1500-W2-50T | 1500x125x88 | 156x13x9.5 | 158x28x31 | 6 | 2.5 | 17.0 |
| SF04-1500-W2-60T | 1500x125x88 | 156x13x9.5 | 158x28x31 | 6 | 2.5 | 17.0 |