

**INKGIANT®**  
Focus on inkjet printing solution

🌐 [www.inkgiant.com.cn](http://www.inkgiant.com.cn)  
✉ [info@inkgiant.com.cn](mailto:info@inkgiant.com.cn)  
☎ 86-0371-5596-0872  
Zhengzhou Bigfoot Digital Technology Co., Ltd

**INKGIANT®**  
Focus on inkjet printing solution




**DTF PRINTER**  
**BF-60E4-S1 DTF SOLUTION**





# BF-60E4-S1 DTF PRINTER



■ Exquisite design ■ Fashionable appearance ■ Cost-Effective

Model	BF-60E4-S1
Print head	4pcs epson head I3200-A1
Control board	Hoson board
Resolution	4Pass:720*1200DPI
	6Pass:720*1800DPI
	8Pass:720*2400DPI
Speed	15-22m <sup>2</sup> /h
Color	CMYK+White
Color control	ICC color profile with adjust function
Print width	600mm
Ink	Water based pigment ink
Operation Enviroment	The temperature is 15°C-30°C, and the relative humidity is 50%-75%
Power	50HZ/60HZ/220V, Printer 2200w/10A, Oven 6500w/22A
Operating system	Windows7 or Above
Image format	Tiff, Jpeg, Bitmap, Eps, Pdf
Software	Flexiprint
Data interface	Gigabit network card
Machine size	Printer size:2420*760*870mm(L*W*H)
	Automatic powder shaker size:1880*1000*1190mm(L*W*H)
Weight	Printer net weight:250KG
	Automatic powder shaker net weight: 285KG



# DTF PRINTER



press paper wheel

Tension rubber roller  
(optional)

- Apply to nylon, chemical fiber, cotton, leather, swimsuit, diving suit.




T-shirt hoodie




Canvas bag



Bolster



Shoes



Intelligent ink-circulation system :  
speed adjustable auto



2 Colors + 2 White



White ink stirring and circulation system  
Stirrer : avoid of head blocking  
Ink tank alarm device



Inktank arlam device  
Monitor the ink lacking in tank



Ink shunt :avoid of ink bubbles to  
print smoothly



Independent ink cartridge  
stable ink supply




# Powder Shaker-S1

## Automatic powder recycling system





## Built-in smoke filter, Oil fume separation



Upgraded suction function, from integration to mesh belt and suction air separation, reducing heat loss.

Lengthened drying tunnel and distributed heating tubes up and down for more even drying.



Desktop platform design of shaker, convenient operation

Integrated circuit (touch screen operation), simple circuit, digital functions





# INK



Colour:	C、M、Y、K+W Cleaning soluton for DTF printer
Shelf life:	color ink 12months, white ink 9 months
Optional packing:	5Kg/bot,1KG/bot,500ml/bot,100ml/bot etc.
Storage temperature:	5°C-35°C
Recommended temperature(printing):	15°C-25°C
Humidity(printing):	45%-75%
Packing size:	460*370*240mm,1KG/BOT, 20BOT/carton
Gross weight :	23KG
Net weight:	20KG

- High whiteness,strong coverage;
- High color density and color reproduction;
- Excellent ink fluency,continuous printing for a long time without ink breakage;
- Friendly and no damage to the print head;
- Good quick-drying performance,not easy to dry in head surface,no flowing on film;
- Soft hand feeling,perfect tensile property and resilience;
- Dry/wet rubbing, washing and perspiration fastness 4-5 grade;





# FILM/POWDER


Instant peel



Product name	INKGIANT DTF film
Product category	Double matte hot peel film
Size	60cm*100m/Roll
Thickness	75um

Packing size: 2rolls/carton Net weight : 14KG Gross weight : 16KG

- Easy to peel off
- Non adherent powder
- Bright color and high color transfer rate
- Excellent ink absorption performance
- No film slipping during printing
- Uniform coating and clear printing




- 100% TPU,stable quality
- Good washing fastness
- Good elasticity, stretch without cracking
- Aluminum foil bag packing,
- moisture proof,safe transportation

Packing size:	1KG/BAG, 20BAG/carton
Net weight :	20KG
Gross weight :	22KG


Type	Model	Melting range	Size	Refer time (s)	Features	Fastness levels (☆ half star)	Hand feeling	Suitable fabric	Washable Washing/dry cleaning
TPU	Middle size	120°-130°	120-250	6-8s	Strong firmness, good toughness,good pulling force	★★★☆	★★	cotton cloth, non-sublimation, polyester cloth	40°C Excellet/60°C good
	Fine size	110°-130°	80-170	6-8s	Low temperature, soft touch,smooth melting surface	★★★★	★★★★	cotton cloth, non-sublimation, polyester cloth	40°C Excellet /60°C ok
	Ultra soft	130°-140°	120-250	6-8s	Best hand feeling	★★★★	★★★★★	cotton cloth, non-sublimation, polyester cloth	40°C Excellet /60°C ok
	Anti-sub black	130°-150°	120-250	6-8s	Applied to,Sublimation Black, Fabric	★★★★	★☆☆	Sublimable black polyester fabric	40°C Excellet /60°C ok
	Anti-sub white	130°-150°	120-250	6-8s	Applied in, Sublimation fabric	★★★★	★☆☆	Sublimable polvester fabric(unlimited color)	40°C Excellet /60°C ok



# Heat press machine



Horizontal plate up slide penumatic double station heat press machine




Facades display

Size:	60*40CM
Power:	3.8KW
Package size:	137*80*70
Gross weight:	170kg

size (cm)	Voltage (V)	Power (KW)	Time rang (Sec)	Temperature (°C)	Working pressure (kg/cm2)	Packaging (cm)
38*38	220	2.2	0-999	0-399	0-8	88*75*60
40*50	220	3	0-999	0-399	0-8	116*73*60
40*60	220/380	3.7	0-999	0-399	0-8	137*75*60
50*60	220/380	3.8	0-999	0-399	0-8	136*83*62
50*70	220/380	4	0-999	0-399	0-8	160*90*60
60*80	220/380	6	0-999	0-399	0-8	175*90*62
70*90	220/380	6	0-999	0-399	0-8	175*90*62
80*100	220/380	9	0-999	0-399	0-8	175*90*62



Vertical up slide penumatic double station heat press machine



Facades display

Size:	40*60CM
Power:	3.8KW
Package size:	103*90*78
Gross weight:	170kg

- Digital control meter makes data input much easier and control time and temperature precision.
- Built-in counter to record production capacity.
- Adopt brand electronic components: F.R.L, relay, switch, air cylinder etc.
- Air pressure can be adjusted according to material thickness.
- 100x125mm powerful cylinder to generate even and stable pressure.
- 2 stainless rod Dia.50mm and 30mm to make machine running very stable and smooth.
- U shaped Heating elements was casted in aluminum to provide even temperature.
- Equipped with two infrared ray to help position article (optional).



# Operation process



Import the processed pictures into the computer

01



Print with printer

02




03

Sprinkle the powder and shake the powder into the drying tunnel to melt it



04

Use Heat press machine pressing



05

No need to wait to tear off the film, OS hot peel



06

Finished product display