

BOPP Soft Touch Film

(HWCMP62-103) 2025/03/02

1. Product Overview & Applications

BOPP Soft Touch Film is a premium biaxially oriented polypropylene film with a unique velvet-like texture, providing a luxurious tactile experience. It offers excellent durability, scratch resistance, and enhanced visual appeal, making it ideal for high-end packaging and printing applications. The film is designed for both decorative and protective uses, ensuring a refined and sophisticated finish.

- Luxury Packaging: Ideal for high-end product boxes, shopping bags, and premium gift wrapping.
- Book Covers & Magazines: Enhances the feel and durability of printed materials.
- Cosmetic & Personal Care Packaging: Adds an elegant, soft-touch effect to product packaging.
- Advertising & Branding: Used for business cards, brochures, and high-quality marketing materials.

2. Technical Specifications

| Parameter | Test Method | Unit | Typical Value |
|----------------------------|-------------|-------|---------------|
| Thickness | ASTM D374 | μm | 30 +/-2 |
| Density | ASTM D1505 | g/cm³ | 0.90 |
| Light Transmission | ASTM D1003 | % | ≥ 90 |
| Haze | ASTM D1003 | % | ≤ 8 |
| Tensile Strength (MD/TD) | ASTM D882 | MPa | 120/240 |
| Elongation (MD/TD) | ASTM D882 | % | 160/65 |
| Coefficient of Friction | ASTM D1894 | - | ≤ 0.3 |
| Surface Tension | ASTM D2578 | mN/m | ≥ 38 |
| Temperature Resistance | = | ° C | -20 to 120 |

3. Additional Features

4. Storage & Handling

- Soft Touch Feel: Provides a silky, smooth texture, enhancing product appeal.
- Excellent Durability: Resistant to scratches and fingerprints. 40% to 60%.
- Eco-friendly: Complies with food contact safety standards and

- For optimal performance, use as soon as possible after opening.

- Store in a dry, ventilated environment, avoiding direct sunlight.--Recommended storage temperature: 10° C to 30° C, relative humidity:

is free from harmful substances.

- High Transparency: Ensures clear and vibrant print quality.
- Good Heat Sealability: Suitable for various packaging applications.

Hardvogue Limited

Address: Xixi Shouzuo, Wenyi Road, West Lake District, Hangzhou City, China 310030

Email: sales@hardvogueltd.com

Website: www.hardvogue.com