

L-TCR-B25
扣管机
Crimping machine



技术参数 TECHNICAL SPECIFICATIONS

| | |
|----------------------------------|-------------------------|
| 胶管扣压范围/Crimping range (mm/inch) | 10-45mm |
| 收扩范围/Maximum opening | 1/4 - 3/4 |
| 扣压控制精度/Accuracy | 0.05 |
| 最大油压/Oil Pump Perssure | 70mpa |
| 配套模具/Dies supplied | 10,12,14,16,19,23,27,31 |
| 整机重量/Weight | 30kg |
| 体积/Dimension | 380*330*280mm |

L-TCR-B51
扣管机
Crimping machine



技术参数 TECHNICAL SPECIFICATIONS

| | |
|---------------------------|--|
| 扣压最大胶管内径/Max Crimping Dia | 2" (1-4SP hoses) |
| 收扩范围/Maximum opening | +25mm |
| 扣压控制精度/Accuracy | 0.1-0.2mm |
| 最大油压/Oil Pump Perssure | 21MPa |
| 扣压力/Crimping Force (T) | 60T |
| 电机功率/Electromotor Power | 4kw |
| 电压/Voltage | 220V/380V |
| 配套模具/Dies supplied | 14,16,19,22,26,30,34,39,45,51,57,63,69 |
| 重量/Weight | 模具架/Mold shelf 80kg 机器/Machine 275kg |
| 体积/Dimension | 模具架/Mold shelf 800*760*500mm 机器/Machine 830*660*900mm |

L-TCR-B32
扣管机
Crimping machine



技术参数 TECHNICAL SPECIFICATIONS

| | |
|---------------------------|-------------------------------------|
| 扣压最大胶管内径/Max Crimping Dia | 1-1/4" (1-4SP hoses) |
| 收扩范围/Maximum opening | +25mm |
| 扣压控制精度/Accuracy | 0.1-0.2mm |
| 最大油压/Oil Pump Perssure | 21MPa |
| 扣压力/Crimping Force (T) | 40T |
| 电机功率/Electromotor Power | 3kw |
| 电压/Voltage | 220V/380V |
| 配套模具/Dies supplied | 10,12,14,16,19,23,27,31,36,41,47,54 |
| 整机重量/Weight | 210kg |
| 体积/Dimension | 830*650*850mm |

L-LCR-B140
扣管机
Crimping machine



技术参数 TECHNICAL SPECIFICATIONS

| | |
|---------------------------|--|
| 扣压最大胶管内径/Max Crimping Dia | 2" (1-6SP hose) |
| 收扩范围/Open and close range | +50mm |
| 扣压控制精度/Crimping accuracy | 0.1-0.2mm |
| 最大油压/Oil Pump Perssure | 31.5mpa |
| 扣压力/Crimping Force (T) | 225T |
| 电机功率/Electromotor Power | 5.5KW |
| 电压/Voltage | 380-440V |
| 配套模具/Dies supplied | 14,16,19,22,26,30,34,39,45,51,57,63,69 |
| 整机重量/Weight | 1250kg |
| 体积/Dimension | 900*1050*1650mm |

L-LSK-B51
剥管机
Skiving machine



| 技术参数 | TECHNICAL SPECIFICATIONS |
|-------------------------|--|
| 剥管范围/Skiving range | φ4 ~ φ70mm |
| 配套芯棒/Supporting mandrel | 内12,16,20,24,32 外04,05,06,08,10,12,16,20,24,32 |
| 电压/Standard Voltage | 380V/220V |
| 电机功率/Electromotor Power | 0.4KW |
| 主轴转速/Spindle speeds | 288 r/min |
| 整机重量/Weight | 105kg |
| 体积/Dimension | 760*570*1230mm |
| 特点/Characteristic | 剥内胶主轴旋转, 剥外胶主轴不旋转 Spindle rotate in skiving inner rubber, Spindle non-rotation in skiving outer rubber |
| 适用范围/Application: | 2 wire, 4 wire, 6 wires |

L-LCU-B51
切管机
Cutting machine



| 技术参数 | TECHNICAL SPECIFICATIONS |
|----------------------------|------------------------------|
| 切管范围/Cutting range | φ4 ~ φ70mm |
| 刀盘(mm)/Blade Diameter | 350*3*51 |
| 电压/Standard Voltage | 380V/220V |
| 电机功率/Electromotor Power | 3KW |
| 气源/Pneumatic Input (Mpa) | 0.5 ~ 0.8 |
| 整机重量/Weight | 190kg |
| 体积/Dimension | 1000*570*1600mm |
| 特点/Characteristic | L-LCU-B51气动式/ Pneumatic type |
| 适用范围/Application: | 2 wire, 4 wire, 6 wires |

L-LCR-B75M
L-LCR-B75C
扣管机
Crimping machine



| 技术参数 | TECHNICAL SPECIFICATIONS |
|----------------------------------|---|
| 胶管扣压范围/Crimping range (mm/inch) | φ6 ~ φ76mm (1/4" ~ 3") |
| 收扩范围/Maximum opening | +60mm |
| 扣压控制精度/Accuracy | 0.02mm |
| 最大油压/Oil Pump Pressure | 31.5MPa |
| 电机功率/Electromotor Power | 4kw |
| 电压/Voltage | 380V |
| 配套模具/Dies supplied | 14,17,20,24,28,33,38,44,50,56,62,68,74 |
| 整机重量/Weight | 1300kg |
| 体积/Dimension | 1000×800×1600(mm) |
| 特点/Characteristic | L-LCR-B75M 电机控制/ELECTRIC CONTROL L-CR-B120C PLC控制/PLC CONTROL |
| 适用范围/Application: | 可扣压各类工程机械胶管、工业设备胶管、汽车胶管、金属管等/Crimping rubber hose of engineering machinery, industry equipment, car equipment and metal tube. |

L-LCU-B32M
手动切管机
Cutting machine



| 技术参数 | TECHNICAL SPECIFICATIONS |
|-------------------------|--------------------------|
| 切管范围/Cutting range | φ4 - φ65mm |
| 刀片直径/Blade Dia | 300mm |
| 转速/Rotate Speed | 2800 r/min |
| 电压/Standard Voltage | 380V 220V |
| 电机功率/Electromotor Power | 2.2KW |

L-LCR-B203

立式扣管机

Vertical Crimping Machine



技术参数 TECHNICAL SPECIFICATIONS

| | |
|-----------------------------------|--|
| 扣压范围/Open and close range | 250mm |
| 最大油压/Oil Pump Pressure | 31.5Mpa |
| 扣压力/Crimping Force (KN/T) | 5000KN/500T |
| 电机功率/Electromotor Power | 5.5kw |
| 电压/Voltage | 380V |
| 工业用管/Industrial | 8"(10") |
| 行程/Opening | 150mm |
| 最大开口直径(无模具时)/Opening without dies | 445mm |
| 液压油/Oil | 400l |
| 整机重量/Weight | 3600KG |
| 体积/Dimension | 830*1840*2200 (净尺寸/Net Measurement) |
| | 900*1900*2350 (带包装/Measurement With Packaging) |
| 配套模具/Dies supplied | 52,63,66,69,78,81,88,118,146,172,178,235 |

注：扣压刀片为常规配置,订购前请确认一下。

Note: Crimping dies are general configuration, please confirm the sizes before order.